

料表编号：6*1梁

☐ 绑扎

☐ 配料

☐ 留存

中国建筑工程总公司

项目名称：平舆

构件部位：6段_-1层-1.00梁6+7段

相同层数：1

序号	分类	Φ6	Φ8	Φ10	Φ12	Φ14	Φ16	Φ18	Φ20	Φ22	Φ25	合计
1	重量	630	10558	9959	8005	4153	1705	916	5183	6842	46589	94.540
2	套筒						16	12	82	82	706	898
3	搭接				286		4					290

注:重量单位明细为公斤、合计为吨；接头单位为个。

日期：2018年03月01日
















钢筋配料表

料单编号:6*1梁

项目名称: 平舆

部位: 6段_1层-1.00梁6+7段






















构件名称	级直 别径	钢筋简图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
6+7段-1.00层非人防: 1~6#为X方向 4级 32*d						
1#KL20 (5-8)	Φ25		9000 9000 8050	1	100.2 9	上1排(通长) 长:25400
	Φ25		8050 9000 9000	1	100.2 9	上1排(通长) 长:25400
	Φ25		3680	4	56.67	上1排(支座5右)
	Φ25		2950	6	68.14	上2排(支座5右)
	Φ25		2950	5	56.79	上3排(支座5右)
	Φ25		6230	4	95.94	上1排(支座6)
	Φ25		4830	6	111.5 7	上2排(支座6)
	Φ25		4830	2	37.19	上3排(支座6)
	Φ25		5600	4	86.24	上1排(支座7)
	Φ25		4360	6	100.7 2	上2排(支座7)
	Φ22		4360	3	38.98	上3排(支座7)
	Φ25		3330	4	51.28	上1排(支座8左)
	Φ20		2630	3	19.49	上2排(支座8左)
	Φ12		3100	2	5.51	架立筋(1跨)
	Φ12		2450	2	4.35	架立筋(2跨)
	Φ12		2740	2	4.87	架立筋(3跨)
	Φ12		8780	8	62.37	腰筋(1跨)

审核:

翻样:





















第 1 页,共76页 2018/3/1 15:52




















构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ12		7780	16	110.54	腰筋(2跨)8,(3跨)8
	Φ25		9000 1030	6	231.69	下2排(1跨) 长:9370
	Φ25		9000 1030	7	270.31	下1排(1跨) 长:9370
	Φ25		9000	2	69.30	下2排(2跨)
	Φ25		9000	7	242.55	下1排(2跨)
	Φ25		9030	6	208.59	下2排(3跨)3,(3跨)3
	Φ25		9030	7	243.36	下1排(3跨)4,(3跨)3
	Φ18		3620	2	14.48	(跨1)2
	Φ20		3700	2	18.28	(跨1)2
	Φ16		3310	4	20.92	(跨2)4
	Φ14		3230	4	15.63	(跨3)4
	Φ10		3180	86	168.74	@100(4)1跨84+2
	Φ10		2780	86	147.51	1跨84+2
	Φ10		2980	152	279.48	@100(4)2跨74+2,3跨74+2
	Φ10		2580	152	241.96	2跨74+2,3跨74+2
	Φ8		540	452	96.41	
2#KL21 (5-8)	Φ25		9000 9000 8050	1	100.29	上1排(通长) 长:25390
	Φ25		8050 9000 9000	1	100.29	上1排(通长) 长:25390
	Φ25		3680	4	56.67	上1排(支座5右)
	Φ25		2950	6	68.14	上2排(支座5右)

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		2950	5	56.79	上3排(支座5右)
	Φ25		6230	4	95.94	上1排(支座6)
	Φ25		4830	6	111.5 7	上2排(支座6)
	Φ25		5560	4	85.62	上1排(支座7)
	Φ25		4330	6	100.0 2	上2排(支座7)
	Φ25		3330	4	51.28	上1排(支座8左)
	Φ20		2630	3	19.49	上2排(支座8左)
	Φ12		3100	2	5.51	架立筋(1跨)
	Φ12		2450	2	4.35	架立筋(2跨)
	Φ12		2750	2	4.88	架立筋(3跨)
	Φ12		8780	8	62.37	腰筋(1跨)
	Φ12		7780	16	110.5 4	腰筋(2跨)8,(3跨)8
	Φ25		9000 1030	2	77.23	下2排(1跨) 长:9700
	Φ25		1030 9000	2	77.23	下2排(1跨) 长:9700
	Φ25		9000 1030	4	154.4 6	下1排(1跨) 长:9700
	Φ25		1030 9000	3	115.8 5	下1排(1跨) 长:9700
	Φ25		9000	2	69.30	下2排(2跨)
	Φ25		9000	7	242.5 5	下1排(2跨)
	Φ25		9030	4	139.0 6	下2排(3跨)2,(3跨)2
	Φ25		9030	7	243.3 6	下1排(3跨)4,(3跨)3
	Φ14		3230	6	23.45	(跨1)4,(跨3)2

审核:






















翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ20		3460	4	34.18	(跨2)4
	Φ12		3160	2	5.61	(跨3)2
	Φ10		2980	238	437.60	@100(4)1跨84+2,2跨74+2,3跨74+2
	Φ10		2580	238	378.86	1跨84+2,2跨74+2,3跨74+2
	Φ8		540	452	96.41	
3#KL22 (5-8)	Φ25		9000 9000 8050	1	100.29	上1排(通长) 长:25390
	Φ25		8050 9000 9000	1	100.29	上1排(通长) 长:25390
	Φ25		3680	4	56.67	上1排(支座5右)
	Φ25		2950	6	68.14	上2排(支座5右)
	Φ25		2950	3	34.07	上3排(支座5右)
	Φ25		6240	4	96.10	上1排(支座6)
	Φ25		4840	6	111.80	上2排(支座6)
	Φ20		4840	2	23.91	上3排(支座6)
	Φ25		5560	4	85.62	上1排(支座7)
	Φ25		4330	6	100.02	上2排(支座7)
	Φ25		3330	4	51.28	上1排(支座8左)
	Φ20		2630	2	12.99	上2排(支座8左)
	Φ12		3100	2	5.51	架立筋(1跨)
	Φ12		2450	2	4.35	架立筋(2跨)
	Φ12		2750	2	4.88	架立筋(3跨)

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ12		8780	8	62.37	腰筋(1跨)
	Φ12		7780	16	110.5 4	腰筋(2跨)8,(3跨)8
	Φ25		9000 1030	3	115.8 5	下2排(1跨) 长:9700
	Φ25		1030 9000	2	77.23	下2排(1跨) 长:9700
	Φ25		9000 1030	4	154.4 6	下1排(1跨) 长:9700
	Φ25		1030 9000	3	115.8 5	下1排(1跨) 长:9700
	Φ25		9000	2	69.30	下2排(2跨)
	Φ25		9000	7	242.5 5	下1排(2跨)
	Φ25		9030	4	139.0 6	下2排(3跨)2,(3跨)2
	Φ25		9030	7	243.3 6	下1排(3跨)4,(3跨)3
	Φ14		3230	2	7.82	(跨1)2
	Φ16		3310	2	10.46	(跨1)2
	Φ20		3460	8	68.37	(跨2)4,(跨3)4
	Φ10		2980	238	437.6 0	@100(4)1跨84+2,2跨74+2,3跨74+2
	Φ10		2580	238	378.8 6	1跨84+2,2跨74+2,3跨74+2
	Φ8		540	452	96.41	
4#KL23 (2-5-2-8)	Φ25		9000 9000 8120	1	100.5 6	上1排(通长) 长:25460
	Φ25		8120 9000 9000	1	100.5 6	上1排(通长) 长:25460
	Φ25		3680	4	56.67	上1排(支座2-5右)
	Φ25		2950	6	68.14	上2排(支座2-5右)

审核:
















翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		2950	4	45.43	上3排(支座2-5右)
	Φ25		6230	4	95.94	上1排(支座2-6)
	Φ25		4830	6	111.5 7	上2排(支座2-6)
	Φ25		4830	2	37.19	上3排(支座2-6)
	Φ25		5560	4	85.62	上1排(支座2-7)
	Φ25		4330	5	83.35	上2排(支座2-7)
	Φ25		3430	4	52.82	上1排(支座2-8左)
	Φ25		2800	5	53.90	上2排(支座2-8左)
	Φ12		3100	2	5.51	架立筋(1跨)
	Φ12		2450	2	4.35	架立筋(2跨)
	Φ12		2750	2	4.88	架立筋(3跨)
	Φ12		8780	8	62.37	腰筋(1跨)
	Φ12		7780	16	110.5 4	腰筋(2跨)8,(3跨)8
	Φ25		9000 1030	3	115.8 5	下2排(1跨) 长:9700
	Φ25		1030 9000	3	115.8 5	下2排(1跨) 长:9700
	Φ25		9000 1030	4	154.4 6	下1排(1跨) 长:9700
	Φ25		1030 9000	3	115.8 5	下1排(1跨) 长:9700
	Φ25		9000	3	103.9 5	下2排(2跨)
	Φ25		9000	6	207.9 0	下1排(2跨)
	Φ25		350 8800	2	70.45	下2排(3跨) 长:8820
	Φ25		8500 650	1	35.23	下2排(3跨) 长:8820




















审核:

翻样:

第 6 页,共76页 2018/3/1 15:52

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		350 8800	3	105.6 8	下1排(3跨) 长:8820
	Φ25		8500 650	3	105.6 8	下1排(3跨) 长:8820
	Φ10		2980	158	290.5 1	@100(4)1跨84,2跨74
	Φ10		2580	158	251.5 1	1跨84,2跨74
	Φ8		2940	74	85.94	@100(4)3跨74
	Φ8		2540	74	74.24	3跨74
	Φ8		540	452	96.41	
5#KL24 (2-5-2-8)	Φ25		9000 9000 8100	1	100.4 8	上1排(通长) 长:25440
	Φ25		8100 9000 9000	1	100.4 8	上1排(通长) 长:25440
	Φ25		3680	4	56.67	上1排(支座2-5右)
	Φ25		2980	6	68.84	上2排(支座2-5右)
	Φ25		6250	4	96.25	上1排(支座2-6)
	Φ25		4850	6	112.0 3	上2排(支座2-6)
	Φ20		4850	2	23.96	上3排(支座2-6)
	Φ25		5560	4	85.62	上1排(支座2-7)
	Φ25		4330	6	100.0 2	上2排(支座2-7)
	Φ20		4330	2	21.39	上3排(支座2-7)
	Φ25		3330	4	51.28	上1排(支座2-8左)
	Φ25		2700	6	62.37	上2排(支座2-8左)
	Φ12		3100	2	5.51	架立筋(1跨)




















构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ12		2450	2	4.35	架立筋(2跨)
	Φ12		2750	2	4.88	架立筋(3跨)
	Φ12		8730	8	62.02	腰筋(1跨)
	Φ12		7780	16	110.5 4	腰筋(2跨)8,(3跨)8
	Φ25		9000 1030	3	115.8 5	下1排(1跨) 长:9700
	Φ25		1030 9000	3	115.8 5	下1排(1跨) 长:9700
	Φ25		9000	5	173.2 5	下2排(2跨)
	Φ25		9000	7	242.5 5	下1排(2跨)
	Φ25		9030	4	139.0 6	下2排(3跨)2,(3跨)2
	Φ25		9030	7	243.3 6	下1排(3跨)4,(3跨)3
	Φ18		3380	8	54.08	(跨2)4,(跨3)4
	Φ8		2940	73	84.77	@100/150(4)1跨17+33+17+6
	Φ8		2540	73	73.24	1跨17+33+17+6
	Φ10		2980	152	279.4 8	@100(4)2跨74+2,3跨74+2
	Φ10		2580	152	241.9 6	2跨74+2,3跨74+2
	Φ8		540	396	84.47	
6#L19 (6-2-7)	Φ14		8700	2	21.05	上1排(通长)
	Φ12		8590	2	15.26	腰筋(通长)
	Φ14		8700	2	21.05	下1排(通长)
	Φ6		1110	50	12.32	@150(2)1跨16,2跨19,3跨15
	Φ6		300	22	1.47	

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
6段-1.00层非人防8~17#为Y方向 4级 32*d						
8#KL8 (2-H-2-K) 2 段	Φ22		9000 9000 1250	1	57.37	上1排(支座2-H左-支座2-K) 长:59940
	Φ22		9000 9000 2330	1	60.58	上1排(支座2-H左-支座2-K) 长:59820
	Φ22		9000 9000	1	53.64	上1排(支座2-H-支座2-K) 长:34710
	Φ22		9000 9000 2390	1	60.76	上1排(支座2-H左-支座2-K) 长:25110
	Φ22		6000 9000 4500	2	116.2 2	上1排(支座2-H左-支座2-K)1,(支座2-H左-支座2-K)1 长:19210
	Φ22		9000 3500	2	74.50	上2排(支座2-H左-支座2-J右) 长:12500
	Φ22		7900	1	23.54	上1排(支座H/J左-支座2-J右)
	Φ22		6950	2	41.42	上2排(支座H/J左-支座2-J右)
	Φ22		4250	1	12.67	上2排(支座2-J)
	Φ22		3250	1	9.69	上1排(支座2-K左)
	Φ22		2620	5	39.04	上2排(支座2-K左)
	Φ12		2900	8	20.60	腰筋(5跨) 长:8610 搭:190
	Φ12		3900	8	27.71	腰筋(5跨) 长:8610 搭:190
	Φ12		4700	16	66.78	腰筋(6跨)
	Φ12		4200	16	59.67	腰筋(7跨)
	Φ14		8550	2	20.69	腰筋(8跨)
	Φ14		8450	18	184.0 4	腰筋(8跨)
	Φ22		3500	4	41.72	下2排(5跨) 长:9410
	Φ22		4500	3	40.23	下2排(5跨) 长:9410

审核:




















翻样:

第 9 页,共76页 2018/3/1 15:52

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ22		3500	5	52.15	下1排(5跨) 长:9410
	Φ22		4500	4	53.64	下1排(5跨) 长:9410
	Φ22		5250	6	93.87	下1排(6跨)
	Φ22		4750	2	28.31	下2排(7跨)
	Φ22		4750	7	99.09	下1排(7跨)
	Φ22		8900	2	53.04	下2排(8跨)
	Φ22		8900	8	212.1 8	下1排(8跨)
	Φ8		4340	37	63.43	@100/150(4)5跨8+27+2
	Φ8		3900	37	57.00	5跨8+27+2
	Φ6		4310	40	38.27	@100(4)6跨39+1
	Φ6		3870	40	34.37	6跨39+1
	Φ12		4420	35	137.3 7	@100(4)7跨34+1
	Φ12		3980	35	123.7 0	7跨34+1
	Φ14		5150	79	492.2 9	@100(4)8跨75+4
	Φ14		4710	79	450.2 3	8跨75+4
	Φ8		580	728	166.7 8	
9#L4 (2-H-2-N) 2 段	Φ25		9000 9000*3 8180	1	170.0 9	上1排(支座2-H左-支座2-N) 长:56270
	Φ25		9000 9000*2 4500 9000 4680	1	173.9 4	上1排(支座2-H左-支座2-N) 长:56270
	Φ25		6100	2	46.97	上1排(支座2-H)

审核:

















翻样:











构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		4680	3	54.05	上2排(支座2-H)
	Φ25		5500	4	84.70	上1排(支座2-J)2,(支座2-K)2
	Φ22		4230	5	63.03	上2排(支座2-J)3,(支座2-K)2
	Φ25		5560	2	42.81	上1排(支座2-L)
	Φ22		4280	3	38.26	上2排(支座2-L)
	Φ25		5960	2	45.89	上1排(支座2-M)
	Φ22		4580	4	54.59	上2排(支座2-M)
	Φ22		4580	2	27.30	上3排(支座2-M)
	Φ12		3100	2	5.51	腰筋(2跨) 长:8910 搭:190
	Φ12		4100	2	7.28	腰筋(2跨) 长:8910 搭:190
	Φ12		8000	8	56.83	腰筋(3跨)4,(5跨)4
	Φ12		7900	4	28.06	腰筋(4跨)
	Φ12		8100	4	28.77	腰筋(6跨)
	Φ12		8700	4	30.90	腰筋(7跨)
	Φ20		3050	2	15.07	下2排(2跨) 长:9050
	Φ20		4050	1	10.00	下2排(2跨) 长:9050
	Φ20		3050	3	22.60	下1排(2跨) 长:9050
	Φ20		4050	3	30.01	下1排(2跨) 长:9050
	Φ20		8120	4	80.23	下2排(3跨)2,(5跨)2
	Φ20		8120	10	200.5 6	下1排(3跨)5,(5跨)5
	Φ20		8020	2	39.62	下2排(4跨)

审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ20		8020	5	99.05	下1排(4跨)
	Φ20		8220	2	40.61	下2排(6跨)
	Φ20		8220	5	101.5 2	下1排(6跨)
	Φ20		8820	6	130.7 1	下2排(7跨)
	Φ20		8820	6	130.7 1	下1排(7跨)
	Φ8		2240	341	301.7 2	@100(2)2跨37,3跨76,4跨75,5跨76,6跨77
	Φ10		2280	83	116.7 6	@100(2)7跨83
	Φ6		400	416	36.94	
10#L18 (2-H-2-N) 2 段	Φ25		9000 9000*3 8070	1	169.6 7	上1排(支座2-H左-支座2-N) 长:83640
	Φ25		9000 9000*2 4500 9000 4600	1	173.6 3	上1排(支座2-H左-支座2-N) 长:83520
	Φ25		6100	2	46.97	上1排(支座2-H)
	Φ25		4680	3	54.05	上2排(支座2-H)
	Φ25		5500	4	84.70	上1排(支座2-J)2,(支座2-K)2
	Φ25		4230	2	32.57	上2排(支座2-J)
	Φ22		4230	2	25.21	上2排(支座2-K)
	Φ25		5560	2	42.81	上1排(支座2-L)
	Φ25		4280	2	32.96	上2排(支座2-L)
	Φ25		5960	2	45.89	上1排(支座2-M)
	Φ25		4580	4	70.53	上2排(支座2-M)

















构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ12		3100	2	5.51	腰筋(5跨) 长:8910 搭:190
	Φ12		4100	2	7.28	腰筋(5跨) 长:8910 搭:190
	Φ12		8000	8	56.83	腰筋(6跨)4,(8跨)4
	Φ12		7900	4	28.06	腰筋(7跨)
	Φ12		8100	4	28.77	腰筋(9跨)
	Φ12		8700	4	30.90	腰筋(10跨)
	Φ20		3050	2	15.07	下2排(5跨) 长:9050
	Φ20		4050	6	60.02	下1排(5跨) 长:9050
	Φ20		8120	4	80.23	下2排(6跨)2,(8跨)2
	Φ20		8120	10	200.5 6	下1排(6跨)5,(8跨)5
	Φ20		8020	2	39.62	下2排(7跨)
	Φ20		8020	5	99.05	下1排(7跨)
	Φ20		8220	2	40.61	下2排(9跨)
	Φ20		8220	5	101.5 2	下1排(9跨)
	Φ20		8820	6	130.7 1	下2排(10跨)
	Φ20		8820	6	130.7 1	下1排(10跨)
	Φ8		2240	233	206.1 6	@100/200(2)5跨12+14,6跨 14+24+14,7跨14+23+14,8跨 14+24+14,9跨14+24+14
	Φ10		2280	83	116.7 6	@100(2)10跨83
	Φ6		400	246	21.84	
11#KL8 (2-H-2-N) 2 段	Φ25		9000 9000*3 7900	1	169.0 1	上1排(支座2-H左-支座2-N) 长:87719

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		9000 9000*3 8900	1	172.8 6	上1排(支座2-H左-支座2-N) 长:87550
	Φ25		6130	2	47.20	上1排(支座2-H)
	Φ25		4780	2	36.81	上2排(支座2-H)
	Φ25		5600	6	129.3 6	上1排(支座2-J)2,(支座2-K)2,(支座2-L)2
	Φ22		4380	2	26.10	上2排(支座2-J)
	Φ25		4380	4	67.45	上2排(支座2-K)2,(支座2-L)2
	Φ25		6030	2	46.43	上1排(支座2-M)
	Φ22		4700	2	28.01	上2排(支座2-M)
	Φ25		3500	2	26.95	上1排(支座2-N左)
	Φ22		2790	2	16.63	上2排(支座2-N左)
	Φ12		2700	2	4.80	腰筋(6跨) 长:8510 搭:190
	Φ12		3700	2	6.57	腰筋(6跨) 长:8510 搭:190
	Φ12		7700	16	109.4 0	腰筋(7跨)4,(8跨)4,(9跨)4,(10跨)4
	Φ12		8350	4	29.66	腰筋(11跨)
	Φ20		3400	1	8.40	下2排(6跨) 长:9400
	Φ20		4400	1	10.87	下2排(6跨) 长:9400
	Φ20		3400	3	25.19	下1排(6跨) 长:9400
	Φ20		4400	3	32.60	下1排(6跨) 长:9400
	Φ20		8600	8	169.9 4	下2排(7跨)2,(8跨)2,(9跨)2,(10跨)2
	Φ20		8600	20	424.8 4	下1排(7跨)5,(8跨)5,(9跨)5,(10跨)5
	Φ20		370 9000	1	23.14	下2排(11跨) 长:9110

审核:

翻样:

第 14 页,共76页 2018/3/1 15:52













构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ20		8800 570	1	23.14	下2排(11跨) 长:9110
	Φ20		370 9000	3	69.43	下1排(11跨) 长:9110
	Φ20		8800 570	2	46.29	下1排(11跨) 长:9110
	Φ8		2240	30	26.54	@100/150(2)6跨16+14
	Φ8		2240	256	226.5 1	@100/200(2)7跨14+22+14,8跨 14+22+14,9跨14+22+14,10跨 14+22+14,11跨14+25+14+3
	Φ6		400	204	18.12	
12#L17 (2-H-2-N) 2 段	Φ25		9000 9000*3 7920	1	169.0 9	上1排(支座2-H左-支座2-N) 长:85511
	Φ25		9000 9000*3 8920	1	172.9 4	上1排(支座2-H左-支座2-N) 长:85380
	Φ25		6100	2	46.97	上1排(支座2-H)
	Φ25		4680	4	72.07	上2排(支座2-H)
	Φ25		5500	4	84.70	上1排(支座2-J)2,(支座2-K)2
	Φ25		4230	2	32.57	上2排(支座2-J)
	Φ22		4230	3	37.82	上2排(支座2-K)
	Φ25		5560	2	42.81	上1排(支座2-L)
	Φ22		4280	3	38.26	上2排(支座2-L)
	Φ25		5930	2	45.66	上1排(支座2-M)
	Φ25		4550	4	70.07	上2排(支座2-M)
	Φ12		3200	2	5.68	腰筋(6跨) 长:8910 搭:190
	Φ12		4100	2	7.28	腰筋(6跨) 长:8810 搭:190
	Φ12		8000	8	56.83	腰筋(7跨)4,(9跨)4

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ12		7900	4	28.06	腰筋(8跨)
	Φ12		8100	4	28.77	腰筋(10跨)
	Φ12		8630	4	30.65	腰筋(11跨)
	Φ20		3150	2	15.56	下2排(6跨) 长:9050
	Φ20		4150	1	10.25	下2排(6跨) 长:9050
	Φ20		3150	3	23.34	下1排(6跨) 长:9050
	Φ20		4150	3	30.75	下1排(6跨) 长:9050
	Φ20		8150	4	80.52	下2排(7跨)2,(9跨)2
	Φ20		8150	10	201.3 1	下1排(7跨)5,(9跨)5
	Φ20		8050	2	39.77	下2排(8跨)
	Φ20		8050	5	99.42	下1排(8跨)
	Φ20		8250	2	40.76	下2排(10跨)
	Φ20		8250	5	101.8 9	下1排(10跨)
	Φ20		9000	6	133.3 8	下2排(11跨)
	Φ20		9000	6	133.3 8	下1排(11跨)
	Φ8		2240	343	303.4 9	@100(2)6跨39,7跨76,8跨75,9跨76,10跨77
	Φ10		2280	84	118.1 7	@100(2)11跨83+1
	Φ6		400	416	36.94	
13#L16 (2-H-2-N) 2 段	Φ25		9000 9000*3 7830	1	168.7 5	上1排(支座2-H左-支座2-N) 长:86960
	Φ25		9000 9000*3 8900	1	172.8 6	上1排(支座2-H左-支座2-N) 长:86831

审核:





















翻样:

第 16 页,共76页 2018/3/1 15:52

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		6100	2	46.97	上1排(支座2-H)
	Φ25		4730	4	72.84	上2排(支座2-H)
	Φ25		5550	6	128.20	上1排(支座2-J)2,(支座2-K)2,(支座2-L)2
	Φ25		4280	2	32.96	上2排(支座2-J)
	Φ22		4280	6	76.53	上2排(支座2-K)3,(支座2-L)3
	Φ25		5930	2	45.66	上1排(支座2-M)
	Φ25		4550	4	70.07	上2排(支座2-M)
	Φ12		3200	2	5.68	腰筋(6跨) 长:8910 搭:190
	Φ12		4200	2	7.46	腰筋(6跨) 长:8910 搭:190
	Φ12		8000	8	56.83	腰筋(7跨)4,(9跨)4
	Φ12		7900	4	28.06	腰筋(8跨)
	Φ12		8100	4	28.77	腰筋(10跨)
	Φ12		9000	8	63.94	腰筋(11跨)
	Φ20		3150	2	15.56	下2排(6跨) 长:9050
	Φ20		4150	1	10.25	下2排(6跨) 长:9050
	Φ20		3150	3	23.34	下1排(6跨) 长:9050
	Φ20		4150	3	30.75	下1排(6跨) 长:9050
	Φ20		8150	4	80.52	下2排(7跨)2,(9跨)2
	Φ20		8150	10	201.31	下1排(7跨)5,(9跨)5
	Φ20		8050	2	39.77	下2排(8跨)
	Φ20		8050	5	99.42	下1排(8跨)

审核:






















翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ20		8250	2	40.76	下2排(10跨)
	Φ20		8250	5	101.89	下1排(10跨)
	Φ20		370 9000	3	69.43	下2排(11跨) 长:9110
	Φ20		8800 560	3	69.36	下2排(11跨) 长:9100
	Φ20		3000 6350	3	69.28	下1排(11跨) 长:9090
	Φ20		4500 4850	3	69.28	下1排(11跨) 长:9090
	Φ8		2240	343	303.49	@100(2)6跨39,7跨76,8跨75,9跨76,10跨77
	Φ10		2280	84	118.17	@100(2)11跨83+1
	Φ6		400	496	44.04	
14#KL7 (2-H-2-N) 2 段	Φ25		9000 9000*3 1880	1	145.84	上1排(支座2-H左-支座2-M右) 长:85880
	Φ25		9000 9000*2 6000 3460	1	140.37	上1排(支座2-H左-支座2-M) 长:82929
	Φ25		6130	2	47.20	上1排(支座2-H)
	Φ25		4780	2	36.81	上2排(支座2-H)
	Φ25		5600	5	107.80	上1排(支座2-J)1,(支座2-K)2,(支座2-L)2
	Φ25		4380	6	101.18	上2排(支座2-J)2,(支座2-K)2,(支座2-L)2
	Φ25		9000 2750	1	45.24	上1排(支座2-M左-支座2-N) 长:11420
	Φ25		2650	1	10.20	上2排(支座2-M左)
	Φ25		2780	1	10.70	上2排(支座2-M左)
	Φ25		8200 1310	1	36.61	上1排(支座2-M-支座2-N) 长:8850
	Φ25		3400	1	13.09	上1排(支座2-M右)

审核:





















翻样:

第 18 页,共76页 2018/3/1 15:52

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		5120	2	39.42	上1排(支座12左-支座2-N)
	Φ12		1350	2	2.40	架立筋(11跨)
	Φ12		2800	2	4.97	腰筋(6跨) 长:8510 搭:190
	Φ12		3800	2	6.75	腰筋(6跨) 长:8510 搭:190
	Φ12		7700	16	109.40	腰筋(7跨)4,(8跨)4,(9跨)4,(10跨)4
	Φ12		6050	8	42.98	腰筋(11跨)
	Φ12		2650	6	14.12	腰筋(12跨)
	Φ22		3600	2	21.46	下2排(6跨) 长:9600
	Φ22		4600	3	41.12	下1排(6跨) 长:9600
	Φ22		3600	2	21.46	下1排(6跨) 长:9600
	Φ22		8750	20	521.50	下1排(7跨)5,(8跨)5,(9跨)5,(10跨)2, (10跨)3
	Φ22		6850	4	81.65	下1排(11跨-12跨)
	Φ22		3750	4	44.70	下1排(12跨)
	Φ8		2240	29	25.66	@100/150(2)6跨15+14
	Φ8		2240	200	176.96	@100/200(2)7跨14+22+14,8跨 14+22+14,9跨14+22+14,10跨 14+22+14
	Φ8		2540	43	43.14	@100/200(4)11跨14+12+14+3
	Φ8		2140	43	36.35	11跨14+12+14+3
	Φ6		2510	24	13.37	@100(4)12跨23+1
	Φ6		2110	24	11.24	12跨23+1
	Φ6		400	166	14.74	
	Φ8		540	78	16.64	

审核:




















翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
15#L15 (2-H-2-M) 2 段	Φ22		9000 9000*2 8430	1	105.5 8	上1排(支座2-H左-支座2-M) 长:81280
	Φ22		9000 9000*2 6000 3430	1	108.5 6	上1排(支座2-H左-支座2-M) 长:81100
	Φ22		6100	3	54.53	上1排(支座2-H)
	Φ22		4680	5	69.73	上2排(支座2-H)
	Φ22		4680	2	27.89	上3排(支座2-H)
	Φ22		5500	6	98.34	上1排(支座2-J)3,(支座2-K)3
	Φ22		4230	7	88.24	上2排(支座2-J)3,(支座2-K)4
	Φ22		5560	3	49.71	上1排(支座2-L)
	Φ22		4280	5	63.77	上2排(支座2-L)
	Φ12		3200	2	5.68	腰筋(6跨) 长:8910 搭:190
	Φ12		4200	2	7.46	腰筋(6跨) 长:8910 搭:190
	Φ12		8000	8	56.83	腰筋(7跨)4,(9跨)4
	Φ12		7900	4	28.06	腰筋(8跨)
	Φ12		8100	4	28.77	腰筋(10跨)
	Φ18		4100	6	49.20	下2排(6跨) 长:9000
	Φ18		3100	6	37.20	下1排(6跨) 长:9000
	Φ18		8100	6	97.20	下2排(7跨)3,(9跨)3
	Φ18		8100	12	194.4 0	下1排(7跨)6,(9跨)6
	Φ18		8000	3	48.00	下2排(8跨)
	Φ18		8000	6	96.00	下1排(8跨)

审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ18		8200	2	32.80	下3排(10跨)
	Φ18		8200	6	98.40	下2排(10跨)
	Φ18		8200	6	98.40	下1排(10跨)
	Φ10		2280	116	163.18	@100(2)6跨39,10跨77
	Φ8		2240	227	200.85	@100(2)7跨76,8跨75,9跨76
	Φ6		400	336	29.84	
16#L14 (2-H-2-M) 2 段	Φ22		9000 9000*2 8400	1	105.49	上1排(支座2-H左-支座2-M) 长:83230
	Φ22		9000 9000*2 6000 3400	1	108.47	上1排(支座2-H左-支座2-M) 长:83070
	Φ22		6100	3	54.53	上1排(支座2-H)
	Φ22		4680	5	69.73	上2排(支座2-H)
	Φ22		4680	5	69.73	上3排(支座2-H)
	Φ22		5500	6	98.34	上1排(支座2-J)3,(支座2-K)3
	Φ22		4230	8	100.84	上2排(支座2-J)4,(支座2-K)4
	Φ22		5560	3	49.71	上1排(支座2-L)
	Φ20		4280	5	52.86	上2排(支座2-L)
	Φ20		4280	2	21.14	上3排(支座2-L)
	Φ12		3200	2	5.68	腰筋(6跨) 长:8910 搭:190
	Φ12		4200	2	7.46	腰筋(6跨) 长:8910 搭:190
	Φ12		8000	8	56.83	腰筋(7跨)4,(9跨)4
	Φ12		7900	4	28.06	腰筋(8跨)

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ12		8100	4	28.77	腰筋(10跨)
	Φ20		3150	2	15.56	下2排(6跨) 长:9050
	Φ20		4150	2	20.50	下2排(6跨) 长:9050
	Φ22		3200	3	28.61	下1排(6跨) 长:9100
	Φ22		4200	2	25.03	下1排(6跨) 长:9100
	Φ25		8250	10	317.6 2	下1排(7跨)5,(9跨)5
	Φ22		8100	2	48.28	下1排(8跨)
	Φ25		8150	3	94.13	下1排(8跨)
	Φ22		8300	5	123.6 7	下2排(10跨)
	Φ22		8300	5	123.6 7	下1排(10跨)
	Φ10		2280	192	270.1 0	@100(2)6跨39,7跨76,10跨77
	Φ8		2240	151	133.6 0	@100(2)8跨75,9跨76
	Φ6		400	336	29.84	
17#KL6 (G-2-H) 1段	Φ22		6080	2	36.24	上1排(支座G-支座2-H)
	Φ14		2000	2	4.84	上1排(支座G右)1,(支座2-H左)1
	Φ12		5150	8	36.59	腰筋(1跨)
	Φ22		5850	4	69.73	下1排(1跨)
	Φ10		2280	39	54.86	@100/150(2)1跨14+11+14
	Φ6		400	56	4.97	
6段接14段人防: (18~24为X主梁、25~30X次梁)						
18#WKL1 (2-4-4/5)	Φ25		7120	2	54.82	上1排(通长)

审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
5段是否做了	Φ12		4500	4	15.98	腰筋
	Φ22		5660	1	16.87	下1排
	Φ25		5830	1	22.45	下1排
	Φ25		5870	1	22.60	下1排
	Φ8		1840	31	22.53	@100/200(2)1跨11+9+11
	Φ6		340	20	1.51	
19#WKL1 (2-4-2-4) 2段 5段是否做了	Φ25		3200	2	24.64	上1排(支座2-4左) 长:8500
	Φ25		4200	2	32.34	上1排(支座2-4左) 长:8500
	Φ12		3430	8	24.37	腰筋(5跨) 长:8340 搭:590
	Φ12		2430	8	17.26	腰筋(5跨) 长:8340 搭:590
	Φ25		3700	2	28.49	下1排(5跨) 长:8870
	Φ25		2700	2	20.79	下1排(5跨) 长:8870
	Φ12		4320	27	103.58	@100(4)5跨27
	Φ12		3920	27	93.99	5跨27
	Φ8		530	104	21.77	
20#KL1 (3/4-2-5)	Φ25		9000 3350	2	95.09	上1排(通长) 长:11690
	Φ25		5920	1	22.79	上1排(支座3/4-支座2-4右)
	Φ25		3350 9000	1	47.55	上1排(通长) 长:11690
	Φ25		4800	1	18.48	上2排(支座3/4-支座2-4右)
	Φ25		3000	2	23.10	上2排(支座3/4-支座2-4)
	Φ25		3350 6720	1	38.77	上1排(支座2-4-支座2-5) 长:9410

审核:





















翻样:

第 23 页,共76页 2018/3/1 15:52

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		2950	1	11.36	上2排(支座2-4右)
	Φ12		2300	4	8.17	腰筋(1跨)
	Φ12		9000 830	8	69.83	腰筋(2跨) 长:9240 搭:590
	Φ25		3380	3	39.04	下1排(1跨)
	Φ25		9000 1060	4	154.9 2	下1排(2跨) 长:9400
	Φ8		2240	19	16.81	@100(2)1跨19
	Φ8		2740	85	92.00	@100(4)2跨84+1
	Φ8		2340	85	78.57	2跨84+1
	Φ6		390	18	1.56	
	Φ8		530	164	34.33	
21#L2 (3/4-4/5)	Φ22		5530 4500	3	89.67	上1排(通长) 长:9740
	Φ22		4500 5530	2	59.78	上1排(通长) 长:9740
	Φ22		3400	3	30.40	上2排(支座2-4)
	Φ12		3250	8	23.09	腰筋(1跨)
	Φ12		6600	8	46.89	腰筋(2跨)
	Φ22		3730	4	44.46	下1排(1跨)
	Φ22		7300	4	87.02	下1排(2跨)
	Φ8		3040	82	98.47	@100(4)1跨24,2跨58
	Φ8		2740	82	88.75	1跨24,2跨58
	Φ6		440	156	15.24	
22#WKL2 (2-4-2-5) 2段	Φ25		2780	2	21.41	上1排(支座2-4左)1,(支座2-4左)1 长:41280

审核:






















翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		3780	1	14.55	上1排(支座2-4左) 长:41280
	Φ25		3700	4	56.98	上1排(支座2-4左)
	Φ25		3000	6	69.30	上2排(支座2-4左)5,(支座2-4左)1
	Φ25		9000 2600	3	133.9 8	上1排(支座2-4-支座2-5) 长:9400
	Φ25		2600 9000	2	89.32	上1排(支座2-4-支座2-5) 长:9400
	Φ25		4720	1	18.17	上1排(支座2-4右)
	Φ25		3420	3	39.50	上2排(支座2-4右)
	Φ25		4120	1	15.86	上1排(支座2-5左)
	Φ25		3420	6	79.00	上2排(支座2-5左)
	Φ25		3420	2	26.33	上3排(支座2-5左)
	Φ12		3070	4	10.90	腰筋(5跨) 长:7880 搭:190
	Φ12		2070	4	7.35	腰筋(5跨) 长:7880 搭:190
	Φ12		9000 830	16	139.6 6	腰筋(6跨) 长:9240 搭:590
	Φ25		2700	2	20.79	下2排(5跨) 长:8870
	Φ25		3700	1	14.24	下2排(5跨) 长:8870
	Φ25		2700	4	41.58	下1排(5跨) 长:8870
	Φ25		3700	4	56.98	下1排(5跨) 长:8870
	Φ25		9000 1110	2	77.85	下2排(6跨) 长:9775
	Φ25		1110 9000	1	38.92	下2排(6跨) 长:9775
	Φ25		9000 1110	4	155.6 9	下1排(6跨) 长:9775
	Φ25		1110 9000	3	116.7 7	下1排(6跨) 长:9775

审核:





















翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		5220	4	80.39	(跨6)
	Φ10		3280	29	58.69	@100(4)5跨29
	Φ10		2740	29	49.03	5跨29
	Φ8		4340	85	145.7 2	@100(4)6跨84+1
	Φ8		3900	85	130.9 4	6跨84+1
	Φ8		580	328	75.14	
	Φ8		630	56	13.94	
23#WKL4 (2-4-2-5) 2段	Φ25		2800	2	21.56	上1排(支座2-4左)1,(支座2-4左)1 长:41280
	Φ25		3800	1	14.63	上1排(支座2-4左) 长:41280
	Φ25		3700	4	56.98	上1排(支座2-4左)
	Φ25		3000	7	80.85	上2排(支座2-4左)
	Φ25		3000	2	23.10	上3排(支座2-4左)
	Φ25		9000 2900	3	137.4 4	上1排(支座2-4-支座2-5) 长:9400
	Φ25		4500 7400	2	91.63	上1排(支座2-4-支座2-5) 长:9400
	Φ25		5020	1	19.33	上1排(支座2-4右)
	Φ25		3420	5	65.83	上2排(支座2-4右)
	Φ25		4120	1	15.86	上1排(支座2-5左)
	Φ25		3420	6	79.00	上2排(支座2-5左)
	Φ25		3420	2	26.33	上3排(支座2-5左)
	Φ12		3070	4	10.90	腰筋(5跨) 长:7880 搭:190
	Φ12		2070	4	7.35	腰筋(5跨) 长:7880 搭:190

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ12		9000 830	14	122.2 1	腰筋(6跨) 长:9240 搭:590
	Φ25		3710	2	28.57	下2排(5跨) 长:8875
	Φ25		2710	4	41.73	下1排(5跨) 长:8875
	Φ25		9000 1110	7	272.4 6	下2排(6跨) 长:9775
	Φ25		1110 9000	7	272.4 6	下1排(6跨) 长:9775
	Φ16		4830	2	15.26	(跨6)2
	Φ25		5220	4	80.39	(跨6)4
	Φ10		3280	29	58.69	@100(4)5跨29
	Φ10		2740	29	49.03	5跨29
	Φ10		4380	86	232.4 1	@100(4)6跨84+2
	Φ10		3940	86	209.0 6	6跨84+2
	Φ8		580	287	65.75	
	Φ8		630	56	13.94	
24#WKL6 (2-4-2-5) 2段	Φ25		2780	2	21.41	上1排(支座2-4左)1,(支座2-4左)1 长:41280
	Φ25		3780	1	14.55	上1排(支座2-4左) 长:41280
	Φ25		3700	4	56.98	上1排(支座2-4左)
	Φ25		3000	4	46.20	上2排(支座2-4左)
	Φ25		9000 2900	3	137.4 4	上1排(支座2-4-支座2-5) 长:9400
	Φ25		4500 7400	2	91.63	上1排(支座2-4-支座2-5) 长:9400
	Φ25		5020	1	19.33	上1排(支座2-4右)
	Φ22		3350	2	19.97	上2排(支座2-4右)






















审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		4120	1	15.86	上1排(支座2-5左)
	Φ25		3450	6	79.69	上2排(支座2-5左)
	Φ12		3070	4	10.90	腰筋(5跨) 长:7880 搭:190
	Φ12		2070	4	7.35	腰筋(5跨) 长:7880 搭:190
	Φ12		8780	14	109.15	腰筋(6跨)
	Φ25		3710	4	57.13	下1排(5跨) 长:8875
	Φ25		2710	4	41.73	下1排(5跨) 长:8875
	Φ25		9000 1110	5	194.62	下2排(6跨) 长:9775
	Φ25		1110 9000	4	155.69	下1排(6跨) 长:9775
	Φ25		5220	2	40.19	(跨6)
	Φ8		3240	25	32.00	@100(4)5跨25
	Φ8		2700	25	26.66	5跨25
	Φ8		4340	75	128.57	@100/200(4)6跨27+15+27+6
	Φ8		3900	75	115.54	6跨27+15+27+6
	Φ8		580	140	32.07	
	Φ8		630	48	11.94	
25#L11 (2-4-2-5) 2段	Φ25		3560	1	13.71	上1排(支座2-4左) 长:40720
	Φ25		2560	1	9.86	上1排(支座2-4左) 长:40720
	Φ25		5480 4500	2	76.85	上1排(支座2-4-支座2-5) 长:9320
	Φ12		3200	2	5.68	腰筋(5跨) 长:8010 搭:190
	Φ12		2200	2	3.91	腰筋(5跨) 长:8010 搭:190

审核:






















翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ12		9000 200	4	32.68	腰筋(6跨) 长:9005 搭:190
	Φ25		2280	1	8.78	下1排(5跨) 长:8280
	Φ25		3280	1	12.63	下1排(5跨) 长:8280
	Φ25		300 9000	2	71.61	下1排(6跨) 长:9300
	Φ8		2240	88	77.86	@100/200(2)5跨8+14+3,6跨 14+29+14+6
	Φ6		390	54	4.68	
26#L8 (2-4-2-5) 2段	Φ25		8280	1	31.88	上1排(支座2-4左-支座4/5) 长:46470
	Φ25		4500 4780	1	35.73	上1排(支座2-4左-支座4/5) 长:46470
	Φ25		5600	2	43.12	上1排(支座2-4)
	Φ22		4330	2	25.81	上2排(支座2-4)
	Φ25		4190	2	32.26	上1排(支座4/5-支座2-5)
	Φ12		3200	2	5.68	腰筋(5跨) 长:8010 搭:190
	Φ12		2200	2	3.91	腰筋(5跨) 长:8010 搭:190
	Φ12		9000	4	31.97	腰筋(6跨-7跨)
	Φ25		2250	2	17.32	下1排(5跨) 长:8250
	Φ25		3250	2	25.02	下1排(5跨) 长:8250
	Φ22		5950	2	35.46	下1排(6跨)
	Φ25		6030	2	46.43	下1排(6跨)
	Φ25		3580	2	27.57	下1排(7跨)
	Φ8		2240	59	52.20	@100(2)5跨30,7跨29
	Φ8		2240	44	38.93	@100/200(2)6跨14+13+14+3

审核:






















翻样:

第 29 页,共76页 2018/3/1 15:52

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ6		390	82	7.10	
27#L7 (2-4-2-5) 2段	Φ25		8350	1	32.15	上1排(支座2-4左-支座4/5) 长:46520
	Φ25		4850 4500	1	36.00	上1排(支座2-4左-支座4/5) 长:46520
	Φ25		5600	2	43.12	上1排(支座2-4)
	Φ22		4330	2	25.81	上2排(支座2-4)
	Φ25		4190	2	32.26	上1排(支座4/5-支座2-5)
	Φ12		3200	2	5.68	腰筋(5跨) 长:8010 搭:190
	Φ12		2200	2	3.91	腰筋(5跨) 长:8010 搭:190
	Φ12		5760	4	20.46	腰筋(6跨)
	Φ12		3310	4	11.76	腰筋(7跨)
	Φ25		2250	2	17.32	下1排(5跨) 长:8250
	Φ25		3250	2	25.02	下1排(5跨) 长:8250
	Φ25		6030	3	69.65	下1排(6跨)
	Φ25		3580	2	27.57	下1排(7跨)
	Φ8		2240	24	21.24	@100/150(2)5跨10+14
	Φ8		2240	44	38.93	@100/200(2)6跨14+13+14+3
	Φ8		2240	29	25.66	@100(2)7跨29
	Φ6		390	72	6.23	
28#L5 (2-4-2-5) 2段	Φ25		8350	1*2	64.29	上1排(支座2-4左-支座4/5) 长:46520
	Φ25		4850 4500	1*2	71.99	上1排(支座2-4左-支座4/5) 长:46520
	Φ25		5600	2*2	86.24	上1排(支座2-4)

审核:







翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ22		4330	2*2	51.61	上2排(支座2-4)
	Φ25		4060	2*2	62.52	上1排(支座4/5-支座2-5)
	Φ12		3200	4*2	22.73	腰筋(5跨) 长:8010 搭:190
	Φ12		5760	4*2	40.92	腰筋(6跨)
	Φ12		3180	4*2	22.59	腰筋(7跨)
	Φ25		3250	3*2	75.07	下2排(5跨) 长:8250
	Φ25		2250	3*2	51.97	下1排(5跨) 长:8250
	Φ25		6030	3*2	139.2 9	下1排(6跨)
	Φ25		3450	2*2	53.13	下1排(7跨)
	Φ8		2240	57*2	100.8 7	@100(2)5跨29,7跨28
	Φ8		2240	44*2	77.86	@100/200(2)6跨14+13+14+3
	Φ6		390	80*2	13.85	
29#L3 (3/4-2-4) 2段	Φ25		2600	1	10.01	上1排(支座2-4左) 长:40770
	Φ25		3600	1	13.86	上1排(支座3/4-支座2-4) 长:40770
	Φ25		4800	1	18.48	上1排(支座3/4左-支座2-4)
	Φ12		2380	4	8.45	腰筋(6跨)
	Φ25		2650	2	20.40	下1排(6跨)
	Φ8		2240	6	5.31	@100/200(2)5跨6
	Φ8		2240	20	17.70	@100(2)6跨20
	Φ6		390	18	1.56	
30#L1 (3/4-2-4) 2段	Φ25		2350	1	9.05	上1排(支座3/4左)













审核:

翻样:

第 31 页,共76页 2018/3/1 15:52

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		3100	3	35.80	上1排(支座3/4-支座2-4)
	Φ12		2310	4	8.21	腰筋(6跨)
	Φ25		2650	2	20.40	下1排(6跨)
	Φ8		2240	6	5.31	@100/200(2)5跨6
	Φ8		2240	19	16.81	@100(2)6跨19
	Φ6		390	18	1.56	






















6段甩13段人防： (31~33为X主梁、34~41X次梁)

31#WKL10 (2-4-2-5) 2段 过580、 1580	Φ25		6650	2	51.20	上1排(支座2-4左)1,(支座2-4左)1 长:41210
	Φ25		5650	1	21.75	上1排(支座2-4左) 长:41210
	Φ25		3680	4	56.67	上1排(支座2-4左)
	Φ25		2980	4	45.89	上2排(支座2-4左)
	Φ25		9000 2900	2	91.63	上1排(支座2-4-支座2-5) 长:9400
	Φ25		2900 9000	1	45.81	上1排(支座2-4-支座2-5) 长:9400
	Φ25		5000	4	77.00	上1排(支座2-4右)
	Φ25		3400	4	52.36	上2排(支座2-4右)
	Φ25		4100	4	63.14	上1排(支座2-5左)
	Φ25		3400	7	91.63	上2排(支座2-5左)
	Φ25		3400	2	26.18	上3排(支座2-5左)
	Φ12		2600	1	2.31	架立筋(5跨)
	Φ12		3200	1	2.84	架立筋(6跨)

审核：

翻样：






















第 32 页,共76页 2018/3/1 15:52

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ12		5650	5	25.09	腰筋(5跨) 长:8360 搭:590
	Φ12		6650	5	29.53	腰筋(5跨) 长:8360 搭:590
	Φ12		9000 830	10	87.29	腰筋(6跨) 长:9240 搭:590
	Φ25		6610	4	101.7 9	下1排(5跨) 长:8875
	Φ25		5610	4	86.39	下1排(5跨) 长:8875
	Φ22		9000 960	1	29.68	下1排(6跨) 长:9670
	Φ25		9000 1110	3	116.7 7	下1排(6跨) 长:9780
	Φ25		1110 9000	3	116.7 7	下1排(6跨) 长:9780
	Φ16		3430	4	21.68	(跨5)4
	Φ8		3240	135	172.7 7	@100(4)5跨47+2,6跨84+2
	Φ8		2700	135	143.9 8	5跨47+2,6跨84+2
	Φ8		630	320	79.63	
32#WKL12 (2-4-2-6) 2段 过540、 1540	Φ25		6570	2	50.59	上1排(支座2-4左) 长:41165
	Φ25		5570	2	42.89	上1排(支座2-4左) 长:41165
	Φ25		3360	3	38.81	上1排(支座2-4左)
	Φ25		2750	7	74.11	上2排(支座2-4左)
	Φ25		2750	2	21.17	上3排(支座2-4左)
	Φ25		2920 9000 9000	2	161.0 8	上1排(支座2-4-支座2-6)1,(支座2-4- 支座2-6)1 长:18420
	Φ25		9000 2950	1	46.01	上1排(支座2-4-支座2-5) 长:9420
	Φ25		2980 9000	1	46.12	上1排(支座2-4-支座2-5) 长:9450
	Φ25		5100	3	58.90	上1排(支座2-4右)

审核:

翻样:






















第 33 页,共76页 2018/3/1 15:52

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		3500	7	94.32	上2排(支座2-4右)
	Φ25		3480	2	26.80	上3排(支座2-4右)
	Φ25		9000 4150	1	50.63	上1排(支座2-5左-支座2-6) 长:12350
	Φ25		3660	1	14.09	上1排(支座2-5左)
	Φ25		4160	1	16.02	上1排(支座2-5左)
	Φ25		2960	4	45.58	上2排(支座2-5左)
	Φ25		3470	3	40.08	上2排(支座2-5左)
	Φ25		2960	2	22.79	上3排(支座2-5左)
	Φ25		3470	2	26.72	上3排(支座2-5左)
	Φ25		9000 2050	1	42.54	上1排(支座2-5-支座2-6) 长:9450
	Φ12		5100	4	18.12	腰筋(5跨) 长:7910 搭:190
	Φ12		6100	4	21.67	腰筋(5跨) 长:7910 搭:190
	Φ12		8700	8	61.80	腰筋(6跨)
	Φ12		9000 780	8	69.48	腰筋(7跨) 长:9190 搭:590
	Φ25		6700	3	77.38	下2排(5跨) 长:8970
	Φ25		5650	2	43.50	下2排(5跨) 长:8920
	Φ25		5700	4	87.78	下1排(5跨) 长:8970
	Φ25		6650	4	102.4 1	下1排(5跨) 长:8920
	Φ25		9000 1050	2	77.38	下2排(6跨) 长:9720
	Φ25		1050 9000	1	38.69	下2排(6跨) 长:9720
	Φ25		9000 1050	4	154.7 7	下1排(6跨) 长:9720

审核:

翻样:

第 34 页,共76页 2018/3/1 15:52

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		1050 9000	4	154.7 7	下1排(6跨) 长:9720
	Φ25		9000 1110	1	38.92	下1排(7跨) 长:9450
	Φ25		9000 1100	2	77.77	下1排(7跨) 长:9770
	Φ25		1100 9000	1	38.88	下1排(7跨) 长:9770
	Φ22		3660	2	21.81	(跨5)2
	Φ16		3430	2	10.84	(跨6)2
	Φ18		3500	2	14.00	(跨6)2
	Φ10		3280	133	269.1 6	@100(4)5跨47+1,6跨83+2
	Φ10		2740	133	224.8 5	5跨47+1,6跨83+2
	Φ12		2620	84	195.4 3	@100(4)7跨84
	Φ12		2220	84	165.5 9	7跨84
	Φ8		530	164	34.33	
	Φ8		630	252	62.71	
33#KL10 (2-4-2-5) 2段 过470、 1470	Φ25		5500	2	42.35	上1排(支座2-4左)1,(支座2-4左)1 长:41170
	Φ25		6500	1	25.02	上1排(支座2-4左) 长:41170
	Φ25		3400	4	52.36	上1排(支座2-4左)
	Φ25		2750	6	63.52	上2排(支座2-4左)
	Φ25		2800	1	10.78	上2排(支座2-4左)
	Φ25		9000 1200	5	196.3 5	上1排(支座2-4-支座2-5) 长:9540
	Φ25		3750	1	14.44	上1排(支座2-4右)
	Φ22		3000	2	17.88	上2排(支座2-4右)


















审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		3710	1	14.28	上1排(支座2-5左)
	Φ25		3050	5	58.71	上2排(支座2-5左)
	Φ12		2800	1	2.49	架立筋(5跨)
	Φ12		5050	4	17.94	腰筋(5跨) 长:7860 搭:190
	Φ12		6050	4	21.49	腰筋(5跨) 长:7860 搭:190
	Φ12		9000 780	14	121.5 8	腰筋(6跨) 长:9190 搭:590
	Φ25		6650	2	51.20	下2排(5跨) 长:8920
	Φ25		5650	2	43.50	下2排(5跨) 长:8920
	Φ25		6650	4	102.4 1	下1排(5跨) 长:8920
	Φ25		5650	4	87.01	下1排(5跨) 长:8920
	Φ22		9000 1010	2	59.66	下1排(6跨) 长:9720
	Φ22		1010 9000	1	29.83	下1排(6跨) 长:9720
	Φ25		9000 1160	2	78.23	下1排(6跨) 长:9825
	Φ25		1160 9000	2	78.23	下1排(6跨) 长:9825
	Φ10		3280	50	101.1 9	@100(4)5跨50
	Φ10		2740	50	84.53	5跨50
	Φ8		4340	84	144.0 0	@100(4)6跨84
	Φ8		3900	84	129.4 0	6跨84
	Φ8		580	287	65.75	
	Φ8		630	92	22.89	
34#L27 (2-4-1/2-10) 2段	Φ25		9000 9000*5 140	1	208.4 4	上1排(支座2-4左-支座1/2-10右) 长:161090






















审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
过1030、 2030	Φ25		6800 9000*4 9000	1	199.4 3	上1排(支座2-4左-支座1/2-10右) 长:161090
	Φ25		6360	1	24.49	上1排(支座2-4左) 长:38180
	Φ25		9000 9000*2 750	1	106.8 4	上1排(支座2-4左-支座2-6右) 长:32000
	Φ25		4800	14	258.7 2	上2排(支座2-4)2,(支座2-5)4,(支座2-6)2,(支座2-8)4,(支座1/2-10)2
	Φ25		3000	2	23.10	上2排(支座2-4左)
	Φ25		7920 9000*3 9000	1	169.0 9	上1排(支座2-4-支座1/2-10) 长:43260
	Φ25		9000 9000*3 7960	1	169.2 5	上1排(支座2-4-支座1/2-10) 长:43300
	Φ25		6150 9000 8770	1	92.09	上1排(支座2-7左-支座1/2-10右) 长:100320
	Φ25		4300	2	33.11	上2排(支座2-7)
	Φ16		5560	2	17.57	腰筋(5跨) 长:8100 搭:260
	Φ16		6560	2	20.73	腰筋(5跨) 长:8100 搭:260
	Φ16		9000	12	170.6 4	腰筋(6跨)4,(7跨)4,(10跨)4
	Φ16		8000	8	101.1 2	腰筋(8跨)4,(9跨)4
	Φ16		4500	2	14.22	腰筋(11跨) 长:7800
	Φ16		3500	2	11.06	腰筋(11跨) 长:7800
	Φ25		5450	2	41.96	下1排(5跨) 长:8250
	Φ25		6450	2	49.66	下1排(5跨) 长:8250
	Φ25		300 8850	12	422.7 3	下1排(6跨)6,(10跨)6 长:9150
	Φ22		300 8850	2	54.53	下1排(7跨) 长:9150






















审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		8850 300	2	70.45	下1排(7跨) 长:9150
	Φ25		8150	10	313.7 7	下1排(8跨)5,(9跨)5
	Φ25		4500	2	34.65	下1排(11跨) 长:7950
	Φ25		3500	1	13.47	下1排(11跨) 长:7950
	Φ10		2280	63	88.63	@100/200(2)5跨18+14+6,11跨14+8+3
	Φ10		2480	300	459.0 5	@100/200(4)6跨14+28+14+6,7跨 14+28+14+6,8跨14+23+14+6,9跨 14+23+14+6,10跨14+28+14+6
	Φ10		2080	300	385.0 1	6跨14+28+14+6,7跨14+28+14+6,8跨 14+23+14+6,9跨14+23+14+6,10跨 14+28+14+6
	Φ6		390	38	3.29	
	Φ8		530	198	41.45	
35#L24 (2-4-2-5) 2段 过530、 1530	Φ25		5500	1	21.17	上1排(支座2-4左) 长:40840
	Φ25		6500	1	25.02	上1排(支座2-4左) 长:19170
	Φ25		9000 810	2	75.54	上1排(支座2-4-支座2-5) 长:9150
	Φ25		3460	2	26.64	上1排(支座2-5左)
	Φ25		2760	4	42.50	上2排(支座2-5左)
	Φ12		5200	2	9.24	腰筋(5跨) 长:8010 搭:190
	Φ12		6200	2	11.01	腰筋(5跨) 长:8010 搭:190
	Φ12		8900	4	31.61	腰筋(6跨)
	Φ25		6100	3	70.45	下2排(5跨) 长:8300
	Φ25		5100	4	78.54	下1排(5跨) 长:8300
	Φ25		350 8800	3	105.6 8	下2排(6跨) 长:9150
	Φ25		8800 350	4	140.9 1	下1排(6跨) 长:9150

审核:





















翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ8		2240	33	29.20	@100/200(2)5跨16+14+3
	Φ10		2280	70	98.47	@100/150(2)6跨14+38+14+4
	Φ6		390	76	6.58	
36#L23 (2-4-2-5) 2段	Φ25		5450	1	20.98	上1排(支座2-4左) 长:40790
	Φ25		6480	1	24.95	上1排(支座2-4左) 长:19150
	Φ25		9000 800	2	75.46	上1排(支座2-4-支座2-5) 长:9140
	Φ25		3480	2	26.80	上1排(支座2-5左)
	Φ22		2740	2	16.33	上2排(支座2-5左)
	Φ12		5200	2	9.24	腰筋(5跨) 长:8010 搭:190
	Φ12		6200	2	11.01	腰筋(5跨) 长:8010 搭:190
	Φ12		8900	4	31.61	腰筋(6跨)
	Φ25		5150	3	59.48	下2排(5跨) 长:8300
	Φ25		6150	4	94.71	下1排(5跨) 长:8300
	Φ25		350 8800	2	70.45	下2排(6跨) 长:9150
	Φ25		8800 350	4	140.9 1	下1排(6跨) 长:9150
	Φ8		2240	99	87.60	@100/200(2)5跨17+14+6,6跨 14+28+14+6
	Φ6		390	64	5.54	
37#L19 (2-4-2-5) 2段	Φ25		5430	1	20.91	上1排(支座2-4左) 长:40770
	Φ25		6430	1	24.76	上1排(支座2-4左) 长:40770
	Φ25		9000 970	1	38.38	上1排(支座2-4-支座2-5) 长:9310
	Φ25		970 9000	1	38.38	上1排(支座2-4-支座2-5) 长:9310

审核:

翻样:





















第 39 页,共76页 2018/3/1 15:52

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		3550	1	13.67	上1排(支座2-5左)
	Φ12		5200	2	9.24	腰筋(5跨) 长:8010 搭:190
	Φ12		6200	2	11.01	腰筋(5跨) 长:8010 搭:190
	Φ12		9000 250	4	32.86	腰筋(6跨) 长:9055 搭:190
	Φ25		5100	3	58.90	下2排(5跨) 长:8300
	Φ25		6100	3	70.45	下1排(5跨) 长:8300
	Φ25		9000 330	4	143.6 8	下1排(6跨) 长:9325
	Φ8		2240	97	85.83	@100/200(2)5跨17+14+3,6跨 14+29+14+6
	Φ6		390	64	5.54	
38#L16 (2-4-2-5) 2段	Φ25		5430	1	20.91	上1排(支座2-4左) 长:40770
	Φ25		6430	1	24.76	上1排(支座2-4左) 长:40770
	Φ25		9000 980	2	76.85	上1排(支座2-4-支座2-5) 长:9320
	Φ25		3550	1	13.67	上1排(支座2-5左)
	Φ12		5200	2	9.24	腰筋(5跨) 长:8010 搭:190
	Φ12		6200	2	11.01	腰筋(5跨) 长:8010 搭:190
	Φ12		9000 250	4	32.86	腰筋(6跨) 长:9060 搭:190
	Φ25		5100	3	58.90	下2排(5跨) 长:8300
	Φ25		6100	3	70.45	下1排(5跨) 长:8300
	Φ25		9000 330	2	71.84	下2排(6跨) 长:9330
	Φ25		9000 330	4	143.6 8	下1排(6跨) 长:9330
	Φ8		2240	97	85.83	@100/200(2)5跨17+14+3,6跨 14+29+14+6

审核:

翻样:

第 40 页,共76页 2018/3/1 15:52

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ6		390	64	5.54	
39#L14 (2-4-2-5) 2段	Φ25		5430	1	20.91	上1排(支座2-4左) 长:40770
	Φ25		6430	1	24.76	上1排(支座2-4左) 长:40770
	Φ25		9000 980	2	76.85	上1排(支座2-4-支座2-5) 长:9320
	Φ12		5200	2	9.24	腰筋(5跨) 长:8010 搭:190
	Φ12		6200	2	11.01	腰筋(5跨) 长:8010 搭:190
	Φ12		9000 200	4	32.68	腰筋(6跨) 长:9005 搭:190
	Φ25		5100	1	19.63	下1排(5跨) 长:8300
	Φ25		6100	1	23.48	下1排(5跨) 长:8300
	Φ25		9000 280	2	71.46	下1排(6跨) 长:9275
	Φ8		2240	97	85.83	@100/200(2)5跨17+14+3,6跨 14+29+14+6
	Φ6		390	64	5.54	
40#KL9 (2-5-5/6)	Φ22		5770	2	34.39	上1排(通长)
-1.00L	Φ22		2080	1	6.20	上1排(支座2-5右)
	Φ22		1710	2	10.19	上2排(支座2-5右)
	Φ12		4780	4	16.98	腰筋
	Φ25		5930	2	45.66	下1排
	Φ8		1840	33	23.98	@100/200(2)1跨11+11+11
	Φ6		340	20	1.51	
41#KL8 (5/6-2-6)	Φ22		3520	2	20.98	上1排(通长)
-1.00L	Φ12		2510	4	8.92	腰筋

审核:

翻样:





















第 41 页,共76页 2018/3/1 15:52

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ22		3520	2	20.98	下1排
	Φ8		1840	21	15.26	@100(2)1跨21
	Φ6		340	20	1.51	
6段左侧Y向-1.9~-1.0人防: (42~43为Y主梁、44~48为Y次梁)						
42#KL12 (2-H-2-N) 1 段	Φ25		2250 6900	1	35.23	上1排(支座2-H-支座2-J) 长:8820
	Φ25		3250 9000*4 2150	1	159.3 9	上1排(支座2-H-支座2-N) 长:40740
	Φ25		2250 9000*4 3250	1	159.7 7	上1排(支座2-H-支座2-N) 长:40840
	Φ25		3250 9000*3 2150	1	124.7 4	上1排(支座2-H-支座2-M) 长:32070
	Φ25		7750	1	29.84	上1排(支座2-J-支座2-K)
	Φ25		9000 9000 5750	1	91.44	上1排(支座2-J-支座2-M) 长:23750
	Φ25		9000 7760	1	64.53	上1排(支座2-L-支座2-N) 长:16425
	Φ22		2720	2	16.21	上2排(支座2-M左)
	Φ25		4000 5470	1	36.46	上1排(支座2-M-支座2-N) 长:9140
	Φ25		5470 4000	1	36.46	上1排(支座2-M-支座2-N) 长:9140
	Φ25		4000 5470	1	36.46	上2排(支座2-M-支座2-N) 长:9140
	Φ25		5470 4000	1	36.46	上2排(支座2-M-支座2-N) 长:9140
	Φ25		3630	2	27.95	上1排(支座2-N右)1,(支座2-N右)1 长:24650
	Φ25		2630	2	20.25	上1排(支座2-N右)1,(支座2-N右)1 长:24650
	Φ25		3480	3	40.19	上1排(支座2-N右)
	Φ25		2780	7	74.92	上2排(支座2-N右)

审核:













翻样:

第 42 页,共76页 2018/3/1 15:52

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		2780	4	42.81	上3排(支座2-N右)
	Φ12		8150	8	57.90	腰筋(1跨)
	Φ14		7000	40	338.80	腰筋(2跨)20,(4跨)20
	Φ12		8310	8	59.03	腰筋(3跨)
	Φ12		8600	8	61.09	腰筋(5跨)
	Φ12		3000	4	10.66	腰筋(6跨) 长:7910
	Φ12		2000	4	7.10	腰筋(6跨) 长:7910
	Φ25		630 8500	4	140.60	下1排(1跨) 长:8800
	Φ25		8500 630	3	105.45	下1排(1跨) 长:8800
	Φ22		7550	6	134.99	下1排(2跨)3,(4跨)3
	Φ25		7750	4	119.35	下1排(2跨)2,(4跨)2
	Φ22		9000	3	80.46	下1排(3跨)
	Φ25		8800 350	4	140.91	下1排(3跨) 长:9150
	Φ25		460 9000	3	109.26	下1排(5跨) 长:9130
	Φ25		8800 660	3	109.26	下1排(5跨) 长:9130
	Φ25		2650	3	30.61	下2排(6跨) 长:8890
	Φ25		3650	2	28.10	下2排(6跨) 长:8890
	Φ25		2650	4	40.81	下1排(6跨) 长:8890
	Φ25		3650	4	56.21	下1排(6跨) 长:8890
	Φ12		2720	147	355.06	@100(4)1跨73,3跨74
	Φ12		2280	147	297.62	1跨73,3跨74





















审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ 14	 2050	5050	124	757.7 0	@100(4)2跨60+2,4跨60+2
	Φ 14	 2050	4650	124	697.6 9	2跨60+2,4跨60+2
	Φ 16	 850	2690	78	331.5 2	@100(4)5跨78
	Φ 16	 850	2290	78	282.2 2	5跨78
	Φ 10	 1100	3280	29	58.69	@100(4)6跨28+1
	Φ 10	 1100	2740	29	49.03	6跨28+1
	Φ 8	 370	530	732	153.2 4	
	Φ 8	 420	580	288	65.98	
	Φ 8	 470	630	56	13.94	
43#WKL3 / (2-G-2-G) 1 段 是否5段已 甩 不做	Φ 25	 2550	3350	2	25.79	上1排(支座2-G右)1,(支座2-G右)1 长:4700
	Φ 25	 1650	2450	2	18.86	上1排(支座2-G右)
	Φ 25	 3550	4350	1	16.75	上1排(支座2-G右) 长:9200
	Φ 12	 1250	1250	1	1.11	架立筋(1跨)
	Φ 12	 4000	4000	4	14.21	腰筋(1跨) 长:4210
	Φ 12	 3000	3000	4	10.66	腰筋(1跨) 长:4210
	Φ 25	 3550	3880	2	29.88	下1排(1跨) 长:4700
	Φ 25	 2550	2880	2	22.18	下1排(1跨) 长:4700
	Φ 8	 850	2540	22	22.07	@100(4)1跨22
	Φ 8	 850	2140	22	18.60	1跨22
	Φ 8	 370	530	44	9.21	
43#WKL37 (2-2-N) 2段	Φ 25	 2150	2150	1	8.28	上1排(支座2左) 长:4700












审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		6450	1	24.83	上1排(支座2-支座2-H) 长:9200
	Φ25		7450	1	28.68	上1排(支座2左-支座2-H) 长:9200
	Φ25		7520	1	28.95	上1排(支座2左-支座2-H)
	Φ25		6150	2	47.35	上1排(支座2-支座2-H)
	Φ25		4500 9000 3450	2	130.5 1	上1排(支座2-H-支座2-K) 长:16950
	Φ25		3450 9000 4500	1	65.26	上1排(支座2-H-支座2-K) 长:16950
	Φ25		3380	4	52.05	上1排(支座2-H右)
	Φ25		2680	1	10.32	上1排(支座2-H左)
	Φ25		2750	5	52.94	上2排(支座2-H右)
	Φ25		2350	2	18.09	上2排(支座2-H左)
	Φ25		5550	4	85.47	上1排(支座2-J)
	Φ25		4300	7	115.8 8	上2排(支座2-J)
	Φ25		3300	4	50.82	上1排(支座2-K左)
	Φ25		2700	3	31.18	上2排(支座2-K左)
	Φ25		3800 9000*2 4800	2	204.8 2	上1排(支座2-K-支座2-N) 长:25000
	Φ25		4800 9000*2 3800	3	307.2 3	上1排(支座2-K-支座2-N) 长:25000
	Φ25		3000 9000	1	46.20	上1排(支座2-K-支座2-L右) 长:11200
	Φ25		9000 1650	1	41.00	上2排(支座2-K-支座2-L右) 长:10650
	Φ25		1650 9000	1	41.00	上2排(支座2-K-支座2-L右) 长:10650
	Φ25		2450	1	9.43	上2排(支座6)




















审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		5860	1	22.56	上1排(支座2-M)
	Φ25		4600	2	35.42	上2排(支座2-M)
	Φ25		3630	2	27.95	上1排(支座2-N右) 长:24980
	Φ25		2630	1	10.13	上1排(支座2-N右) 长:24980
	Φ25		4000	1	15.40	上1排(支座2-N左)
	Φ25		3450	4	53.13	上1排(支座2-N右)
	Φ22		3250	3	29.06	上2排(支座2-N左)
	Φ25		2820	7	76.00	上2排(支座2-N右)
	Φ25		2820	2	21.71	上3排(支座2-N右)
	Φ12		2850	1	2.53	架立筋(3跨)
	Φ12		2700	1	2.40	架立筋(4跨)
	Φ12		800	4	2.84	腰筋(1跨) 长:4210 搭:590
	Φ12		1800	4	6.39	腰筋(1跨) 长:4210 搭:590
	Φ12		4850	16	68.91	腰筋(2跨)
	Φ12		7800	8	55.41	腰筋(3跨)
	Φ12		7600	8	53.99	腰筋(4跨)
	Φ12		4450	14	55.32	腰筋(5跨)
	Φ12		3950	14	49.11	腰筋(6跨)
	Φ12		8200	14	101.9 4	腰筋(7跨)
	Φ12		8550	14	106.2 9	腰筋(8跨)
	Φ12		3000	4	10.66	腰筋(9跨) 长:7910

审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ12		2000	4	7.10	腰筋(9跨) 长:7910
	Φ25		1150	2	8.85	下1排(1跨) 长:4700
	Φ25		2150	2	16.55	下1排(1跨) 长:4700
	Φ22		5500	3	49.17	下1排(2跨)
	Φ25		5750	2	44.27	下1排(2跨)
	Φ25		610 8500	2	70.15	下2排(3跨) 长:8780
	Φ25		8500 610	1	35.07	下2排(3跨) 长:8780
	Φ25		610 8500	4	140.2 9	下1排(3跨) 长:8780
	Φ25		8500 610	4	140.2 9	下1排(3跨) 长:8780
	Φ25		9000	3	103.9 5	下2排(4跨)
	Φ25		9000	8	277.2 0	下1排(4跨)
	Φ22		5150	3	46.04	下1排(5跨)
	Φ25		5350	2	41.19	下1排(5跨)
	Φ22		4650	3	41.57	下1排(6跨)
	Φ25		4850	2	37.34	下1排(6跨)
	Φ22		8900	2	53.04	下1排(7跨)
	Φ25		300 8800	5	175.1 7	下1排(7跨) 长:9100
	Φ25		9000 450	6	218.2 9	下1排(8跨) 长:9450
	Φ25		3700	3	42.73	下2排(9跨) 长:8920
	Φ25		2700	2	20.79	下2排(9跨) 长:8920
	Φ25		3700	4	56.98	下1排(9跨) 长:8920




















审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		2700	4	41.58	下1排(9跨) 长:8920
	Φ16		4940	2	15.61	(跨2)2
	Φ16		3430	6	32.52	(跨3)2,(跨4)4
	Φ18		3500	2	14.00	(跨3)2
	Φ16		4830	8	61.05	(跨7)4,(跨8)4
	Φ8		2540	12	12.04	@100(4)1跨11+1
	Φ8		2140	12	10.14	1跨11+1
	Φ8		4340	266	456.00	@100(4)2跨40+2,5跨36+1,6跨31+1,7跨74+2,8跨77+2
	Φ8		3900	266	409.77	2跨40+2,5跨36+1,6跨31+1,7跨74+2,8跨77+2
	Φ10		3280	179	362.25	@100(4)3跨74+2,4跨72+2,9跨28+1
	Φ10		2740	179	302.61	3跨74+2,4跨72+2,9跨28+1
	Φ8		530	20	4.19	
44#L45 (2-G-2-G) 1 段 是否5段已 甩 不做	Φ25		3800	2	29.26	上1排(支座2-G右) 长:9140
	Φ25		2800	2	21.56	上1排(支座2-G右) 长:9140
	Φ12		4300	8	30.55	腰筋(1跨) 长:9200
	Φ12		3300	8	23.44	腰筋(1跨) 长:9200
	Φ25		3800	3	43.89	下1排(1跨) 长:9620
	Φ25		2800	2	21.56	下1排(1跨) 长:9620
	Φ8		4140	24	39.25	@100/200(4)1跨21+3





















审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ8	 1700	3840	24	36.40	1跨21+3
	Φ6	 320	440	48	4.69	
44#L45 (2-H-2-N) 2 段	Φ25	 5670 380	6000	2	46.20	上1排(支座2-H左) 长:9140
	Φ25	 6670 380	7000	2	53.90	上1排(支座2-H左) 长:9140
	Φ25	 8050 9000*3 9000 套 套 丝	8050 9000*3 9000	1	169.5 9	上1排(支座2-H-支座2-N右) 长:65400
	Φ25	 7050 9000*3 9000 套 套 丝	7050 9000*3 9000	1	165.7 4	上1排(支座2-H-支座2-N右) 长:65400
	Φ25	 5530	5530	2	42.58	上1排(支座2-J)
	Φ25	 4300	4300	2	33.11	上2排(支座2-J)
	Φ25	 9000 9000*2 3070 套 套	9000 9000*2 3070	1	115.7 7	上1排(支座2-K左-支座2-N右) 长:30070
	Φ25	 2900	2900	1	11.16	上1排(支座5)
	Φ25	 2250	2250	2	17.32	上2排(支座5)
	Φ25	 5800	5800	2	44.66	上1排(支座2-M)1,(支座2-N)1
	Φ25	 4500	4500	5	86.62	上2排(支座2-M)3,(支座2-N)2
	Φ12	 5650 搭	5650	8	40.14	腰筋(1跨) 长:9200 搭:590
	Φ12	 6650 搭	6650	8	47.24	腰筋(1跨) 长:9200 搭:590
	Φ12	 7900	7900	12	84.18	腰筋(2跨)4,(3跨)4,(6跨)4
	Φ12	 4300	4300	4	15.27	腰筋(4跨)
	Φ12	 3700	3700	4	13.14	腰筋(5跨)
	Φ12	 8300	8300	4	29.48	腰筋(7跨)
	Φ12	 3100	3100	2	5.51	腰筋(8跨) 长:8010






















审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ12		2100	2	3.73	腰筋(8跨) 长:8010
	Φ25		6150	3	71.03	下1排(1跨) 长:9620
	Φ25		7150	2	55.05	下1排(1跨) 长:9620
	Φ25		8150	12	376.5 3	下1排(2跨)4,(3跨)4,(6跨)4
	Φ25		8150	5	156.8 9	下2排(3跨)2,(6跨)3
	Φ25		4600	2	35.42	下1排(4跨)
	Φ25		4000	2	30.80	下1排(5跨)
	Φ25		8550	2	65.83	下2排(7跨)
	Φ25		8550	4	131.6 7	下1排(7跨)
	Φ25		3200	3	36.96	下2排(8跨) 长:8250
	Φ25		2200	3	25.41	下1排(8跨) 长:8250
	Φ16		2750	4	17.38	(跨4)2,(跨5)2
	Φ8		4140	54	88.31	@100/200(4)1跨6+15+27+6
	Φ8		3840	54	81.91	1跨6+15+27+6
	Φ8		2240	138	122.1 0	@100/200(2)2跨14+23+14+6,3跨 14+23+14+6,8跨14+7+3
	Φ8		2240	70	61.94	@100/150(2)4跨14+7+14+2,5跨 14+3+14+2
	Φ10		2280	116	163.1 8	@100/200(2)6跨14+23+14+6,7跨 14+25+14+6
	Φ6		390	204	17.66	
	Φ6		440	112	10.94	
45#L44 (2-P-2-R) 2 段	Φ25		9000 9000 3680	1	83.47	上1排(支座2-P左-支座2-R) 长:24570

审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		9000 9000 4680	1	87.32	上1排(支座2-P左-支座2-R) 长:24570
	Φ25		5600	2	43.12	上1排(支座2-P)
	Φ25		4400	4	67.76	上2排(支座2-P)2,(支座2-Q)2
	Φ25		9000 2550	1	44.47	上1排(支座2-Q左-支座2-R) 长:11220
	Φ25		5700	1	21.94	上1排(支座2-Q)
	Φ25		3250	1	12.51	上1排(支座2-R左)
	Φ12		5000	2	8.88	腰筋(7跨) 长:8060 搭:190
	Φ12		6000	2	10.66	腰筋(7跨) 长:8060 搭:190
	Φ12		8000	4	28.42	腰筋(8跨)
	Φ12		8150	4	28.95	腰筋(9跨)
	Φ25		5100	1	19.63	下2排(7跨) 长:8300
	Φ25		6100	1	23.48	下2排(7跨) 长:8300
	Φ25		5100	2	39.27	下1排(7跨) 长:8300
	Φ25		6100	2	46.97	下1排(7跨) 长:8300
	Φ25		8250	2	63.52	下2排(8跨)
	Φ25		8250	4	127.0 5	下1排(8跨)
	Φ25		8400	3	97.02	下2排(9跨)
	Φ25		8400	4	129.3 6	下1排(9跨)
	Φ8		2240	92	81.40	@100/200(2)7跨17+14+3,8跨 14+24+14+6
	Φ10		2280	58	81.59	@100/200(2)9跨14+24+14+6
	Φ6		390	96	8.31	

审核:

翻样:












第 51 页,共76页 2018/3/1 15:52

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
46#KL11 (2-G-2) 1段 是否5段已 甩 不做	Φ25		3400	3	39.27	上1排(支座2-G-支座2) 长:5020
	Φ25		4400	2	33.88	上2排(支座2-G-支座2右) 长:5020
	Φ12		2450	4	8.70	腰筋(1跨)
	Φ22		3560	3	31.83	下1排(1跨-2跨)
	Φ8		1840	24	17.44	@100(2)1跨2跨3
	Φ6		340	20	1.51	
46#KL11 (3-3) 2段	Φ25		1950	3	22.52	上1排(支座3左) 长:5020
	Φ25		950	2	7.31	上2排(支座3) 长:5020
	Φ12		1900	4	6.75	腰筋(2跨)
	Φ22		2920	3	26.10	下1排(1跨-2跨)
	Φ8		1840	12	8.72	@100(2)2跨12
	Φ6		340	12	0.91	
47#L45 (1-2-N) 1段	Φ25		4000	1	177.79	上1排(支座1-支座2-N) 长:45520
	Φ25		3000	1	123.97	上1排(支座1-支座2-L右) 长:31870
	Φ25		9000	1	84.93	上1排(支座1-支座2-K) 长:21730
	Φ25		3000	1	177.79	上1排(支座1-支座2-N) 长:45520
	Φ25		2900	3	33.49	上2排(支座2-H左)
	Φ25		4250	2	32.72	上2排(支座2-J)
	Φ25		2900	1	11.16	上1排(支座5)
	Φ25		2250	2	17.32	上2排(支座5)

审核:






















翻样:

第 52 页,共76页 2018/3/1 15:52

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		5800	2	44.66	上1排(支座2-M)
	Φ25		4500	2	34.65	上2排(支座2-M)
	Φ25		3550	1	13.67	上1排(支座2-N右) 长:24570
	Φ25		2550	1	9.82	上1排(支座2-N右) 长:24570
	Φ12		4950	4	17.58	腰筋(1跨)
	Φ12		8400	14	104.4 3	腰筋(2跨)
	Φ12		7950	14	98.83	腰筋(3跨)
	Φ12		4350	4	15.45	腰筋(4跨)
	Φ12		3700	4	13.14	腰筋(5跨)
	Φ12		7900	4	28.06	腰筋(6跨)
	Φ12		8300	4	29.48	腰筋(7跨)
	Φ12		3250	2	5.77	腰筋(8跨) 长:8060
	Φ12		2250	2	4.00	腰筋(8跨) 长:8060
	Φ25		5200	3	60.06	下1排(1跨)
	Φ22		9000	2	53.64	下1排(2跨)
	Φ25		8500 610	2	70.15	下1排(2跨) 长:8780
	Φ25		610 8500	1	35.07	下1排(2跨) 长:8780
	Φ25		8200	2	63.14	下2排(3跨)
	Φ25		8200	5	157.8 5	下1排(3跨)
	Φ25		4600	2	35.42	下1排(4跨)
	Φ25		4000	2	30.80	下1排(5跨)

审核：















翻样：

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		8150	4	125.5 1	下1排(6跨)
	Φ25		8600	4	132.4 4	下1排(7跨)
	Φ25		3200	3	36.96	下2排(8跨) 长:8300
	Φ25		2200	3	25.41	下1排(8跨) 长:8300
	Φ16		2750	2	8.69	(跨4)
	Φ8		2040	46	37.07	@100(2)1跨46
	Φ8		4140	78	127.5 5	@100(4)2跨76+2
	Φ8		3840	78	118.3 1	2跨76+2
	Φ8		4140	70	114.4 7	@100/200(4)3跨27+10+27+6
	Φ8		3840	70	106.1 8	3跨27+10+27+6
	Φ8		2240	101	89.36	@100/150(2)4跨14+8+14+2,6跨 14+31+14+4
	Φ8		2240	117	103.5 2	@100/200(2)5跨14+2+14+3,7跨 14+25+14+6,8跨14+8+3
	Φ6		390	186	16.10	
48#WKL38 (M-M/N)	Φ6		440	385	37.61	
-1.00L	Φ22		5610	2	33.44	上1排(通长)
	Φ22		2040	1	6.08	上1排(支座M右)
	Φ22		1800	2	10.73	上2排(支座M右)
	Φ12		3480	4	12.36	腰筋
	Φ22		4460	2	26.58	下1排
	Φ8		1840	26	18.90	@100/200(2)1跨11+4+11
	Φ6		340	14	1.06	

审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
6段上侧与12段相接向-1.9~-1.0人防：（49为X向梁、50~64为Y梁）						
49#WKL16 (2-7-1/2-10) 1段 过10带 570、1570	Φ25		5000 9000 5850	3	229.2 7	上1排(支座2-7-支座1/2-10) 长:17350
	Φ25		4000 9000 6850	2	152.8 4	上1排(支座2-7-支座1/2-10) 长:17350
	Φ22		3250	2	19.37	上2排(支座2-7右)
	Φ25		5050	3	58.33	上2排(支座2-8)
	Φ25		2400 9000	1	43.89	上1排(支座2-8-支座1/2-10) 长:9700
	Φ25		2950	6	68.14	上2排(支座2-8右)2,(支座1/2-10右)4
	Φ25		4000	3	46.20	上1排(支座1/2-10右) 长:81082
	Φ25		5000	3	57.75	上1排(支座1/2-10右) 长:81082
	Φ25		3600	1	13.86	上1排(支座1/2-10右)
	Φ25		3500	2	26.95	上2排(支座1/2-10左)
	Φ16		8050	16	203.5 0	腰筋(1跨)
	Φ16		9000 320	16	235.6 1	腰筋(2跨) 长:9320
	Φ16		4500	4	28.44	腰筋(3跨) 长:7750
	Φ16		3500	4	22.12	腰筋(3跨) 长:7750
	Φ22		8450	2	50.36	下1排(1跨)
	Φ25		8650	4	133.2 1	下1排(1跨)
	Φ25		9000 950	4	153.2 3	下2排(2跨) 长:9950
	Φ25		950 9000	4	153.2 3	下1排(2跨) 长:9950
	Φ22		4000	1	11.92	下1排(3跨) 长:8572

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ22	330 	5000	1	14.90	下1排(3跨) 长:8572
	Φ25	380 	4050	3	46.78	下1排(3跨) 长:8670
	Φ25	380 	5050	3	58.33	下1排(3跨) 长:8670
	Φ14	 2050	5050	71	433.8 5	@100(4)1跨69+2
	Φ14	 2050	4650	71	399.4 8	1跨69+2
	Φ10	 1700	4380	85	229.7 1	@100(4)2跨82+3
	Φ10	 1700	3940	85	206.6 3	2跨82+3
	Φ10	 1100	3280	28	56.67	@100/200(4)3跨18+7+3
	Φ10	 1100	2740	28	47.34	3跨18+7+3
	Φ8		530	272	56.94	
	Φ8		580	320	73.31	
	Φ8		630	32	7.96	
50#WKL39 (2-N-2-N) 1 段	Φ25	850 	2750	2	21.17	上1排(支座2-N右)
	Φ25	850 	2750	1	10.59	上1排(支座2-N右) 长:10750
	Φ25	850 	3750	1	14.44	上1排(支座2-N右) 长:10750
	Φ12		3000	2	5.33	腰筋(1跨) 长:7810
	Φ12		2000	2	3.55	腰筋(1跨) 长:7810
	Φ25	380 	3250	3	37.54	下2排(1跨) 长:8620
	Φ25	380 	2250	3	25.99	下1排(1跨) 长:8620
	Φ8	 800	2240	20	17.70	@100/200(2)1跨14+6
	Φ6		390	14	1.21	

审核:





















翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
51#WKL40 (2-N-2-N) 1 段	Φ25		4350	2	33.49	上1排(支座2-N右)1,(支座2-N右)1 长:11350
	Φ25		3350	1	12.90	上1排(支座2-N右) 长:8700
	Φ25		4100	1	15.78	上1排(支座2-N右)
	Φ25		3500	3	40.42	上2排(支座2-N右)
	Φ12		2000	2	3.55	腰筋(1跨) 长:7960
	Φ12		3000	2	5.33	腰筋(1跨) 长:7960
	Φ25		2880	2	22.18	下2排(1跨) 长:9200
	Φ25		3880	1	14.94	下2排(1跨) 长:9200
	Φ25		2880	2	22.18	下1排(1跨) 长:9200
	Φ25		3880	2	29.88	下1排(1跨) 长:9200
	Φ10		2280	25	35.17	@100/150(2)1跨14+9+2
	Φ6		390	18	1.56	
52#KL15 (2-M-2-N) 1 段	Φ25		5250 4300	2	73.53	上1排(支座2-M-支座2-N) 长:9220
	Φ25		4300 5250	2	73.53	上1排(支座2-M-支座2-N) 长:9220
	Φ25		2880	2	22.18	上1排(支座2-N右) 长:7750
	Φ25		1880	2	14.48	上1排(支座2-N) 长:7750
	Φ25		2900	3	33.49	上1排(支座2-N右)
	Φ25		2400	6	55.44	上2排(支座2-N右)
	Φ14		8750	4	42.35	腰筋(1跨)
	Φ14		2500	4	12.10	腰筋(2跨) 长:7010
	Φ14		1500	4	7.26	腰筋(1跨) 长:7010

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25	380 8670 550 套	9000 550	2	73.53	下1排(1跨) 长:9220
	Φ25	380 270 9000 套	600 9000	2	73.92	下1排(1跨) 长:9270
	Φ25	1850 丝	1850	6	42.73	下2排(1跨) 长:7750
	Φ25	2850 丝	2850	5	54.86	下1排(2跨) 长:7750
	Φ8	350 850	2540	78	78.26	@100(4)1跨78
	Φ8	150 850	2140	78	65.93	1跨78
	Φ14	450 1150	3450	21	87.66	@100(4)2跨20+1
	Φ14	180 1150	2910	21	73.94	2跨20+1
	Φ8	370	530	76	15.91	
	Φ8	470	630	40	9.95	
55#L40 (2-N-2-N) 1 段	Φ25	380 3070 丝	3400	1	13.09	上1排(支座2-N右) 长:8770
	Φ25	380 2070 丝	2400	1	9.24	上1排(支座2-N右) 长:8770
	Φ12	3250	3250	2	5.77	腰筋(1跨) 长:8080
	Φ12	2250	2250	2	4.00	腰筋(1跨) 长:8080
	Φ25	200 3100 丝	3250	3	37.54	下2排(1跨) 长:8200
	Φ25	200 2100 丝	2250	3	25.99	下1排(1跨) 长:8200
	Φ8	250 800	2240	21	18.58	@100/200(2)1跨14+7
	Φ6	270	390	16	1.39	
54#L4 / (2-N-2-N) 1 段	Φ25	380 3070 丝	3400	1	13.09	上1排(支座2-N右) 长:10970
	Φ25	380 2070 丝	2400	1	9.24	上1排(支座2-N右) 长:10970
	Φ12	3250	3250	2	5.77	腰筋(1跨) 长:8080

审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ12		2250	2	4.00	腰筋(1跨) 长:8080
	Φ25		3250	3	37.54	下2排(1跨) 长:8200
	Φ25		2250	3	25.99	下1排(1跨) 长:8200
	Φ8		2240	25	22.12	@100/200(2)1跨14+8+3
	Φ6		390	16	1.39	
55#WKL42 (2-N-2-N) 1 段	Φ25		3900	2	30.03	上1排(支座2-N右) 长:24450
	Φ25		2900	1	11.16	上1排(支座2-N右) 长:24450
	Φ25		3730	4	57.44	上1排(支座2-N右)
	Φ25		3130	4	48.20	上2排(支座2-N右)
	Φ12		2800	4	9.95	腰筋(1跨) 长:7710
	Φ12		1800	4	6.39	腰筋(1跨) 长:7710
	Φ25		3450	3	39.85	下2排(1跨) 长:8670
	Φ25		2450	2	18.86	下2排(1跨) 长:8670
	Φ25		3450	4	53.13	下1排(1跨) 长:8670
	Φ25		2450	4	37.73	下1排(1跨) 长:8670
	Φ10		3280	27	54.64	@100(4)1跨26+1
	Φ10		2740	27	45.65	1跨26+1
	Φ8		630	52	12.94	
56#L48 (2-N-2-N) 1 段	Φ25		3400	1	13.09	上1排(支座2-N右) 长:24470
	Φ25		2400	1	9.24	上1排(支座2-N右) 长:24470
	Φ12		3000	2	5.33	腰筋(1跨) 长:7960

审核:






















翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ12		2000	2	3.55	腰筋(1跨) 长:7960
	Φ25		3000	3	34.65	下2排(1跨) 长:8200
	Φ25		2000	3	23.10	下1排(1跨) 长:8200
	Φ8		2240	24	21.24	@100/200(2)1跨14+7+3
	Φ6		390	14	1.21	
3/4#L49 (2-N-2-N) 1 段	Φ25		3400	1	13.09	上1排(支座2-N右) 长:24470
	Φ25		2400	1	9.24	上1排(支座2-N右) 长:24470
	Φ12		3000	2	5.33	腰筋(1跨) 长:7960
	Φ12		2000	2	3.55	腰筋(1跨) 长:7960
	Φ25		3000	2	23.10	下1排(1跨) 长:8200
	Φ25		2000	2	15.40	下1排(1跨) 长:8200
	Φ8		2240	24	21.24	@100/200(2)1跨14+7+3
	Φ6		390	14	1.21	
3/4#WKL43 (2-M-2-N) 1 段	Φ25		4050	1	15.59	上1排(支座2-M右)
	Φ25		9000 2550	2	88.93	上1排(支座2-M-支座2-N) 长:9050
	Φ25		2550 9000	1	44.47	上1排(支座2-M-支座2-N) 长:9050
	Φ25		4850	1	18.67	上1排(支座2-N左)
	Φ25		3420	2	26.33	上1排(支座2-N右) 长:24440
	Φ25		2420	1	9.32	上1排(支座2-N右) 长:24440
	Φ25		3300	4	50.82	上1排(支座2-N右)
	Φ25		2700	7	72.76	上2排(支座2-N右)

审核:

翻样:

















第 60 页,共76页 2018/3/1 15:52

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		2700	3	31.18	上3排(支座2-N右)
	Φ12		3050	1	2.71	架立筋(1跨)
	Φ12		8790	8	62.44	腰筋(1跨)
	Φ12		2800	4	9.95	腰筋(2跨) 长:7710
	Φ12		1800	4	6.39	腰筋(2跨) 长:7710
	Φ25		9000 710	2	74.77	下2排(1跨) 长:9050
	Φ25		9000 710	6	224.3 0	下1排(1跨) 长:9050
	Φ25		2420	2	18.63	下2排(2跨) 长:8690
	Φ25		3420	2	26.33	下2排(2跨) 长:8690
	Φ25		2420	4	37.27	下1排(2跨) 长:8690
	Φ25		3420	4	52.67	下1排(2跨) 长:8690
	Φ10		2580	80	127.3 5	@100(4)1跨80
	Φ10		2180	80	107.6 0	1跨80
	Φ10		3280	27	54.64	@100(4)2跨26+1
	Φ10		2740	27	45.65	2跨26+1
	Φ8		530	156	32.66	
	Φ8		630	52	12.94	
59#LSU (2-N-2-N) 1 段	Φ25		3380	1	13.01	上1排(支座2-N右) 长:24400
	Φ25		2380	1	9.16	上1排(支座2-N右) 长:24400
	Φ25		3220	2	24.79	上1排(支座2-N右)
	Φ22		2550	2	15.20	上2排(支座2-N右)

审核:





















翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ12		3000	2	5.33	腰筋(1跨) 长:7810
	Φ12		2000	2	3.55	腰筋(1跨) 长:7810
	Φ25		3000	3	34.65	下2排(1跨) 长:8050
	Φ25		2000	3	23.10	下1排(1跨) 长:8050
	Φ8		2240	23	20.35	@100/200(2)1跨14+6+3
	Φ6		390	14	1.21	
60#L51 (1-2-N) 1段	Φ25		9000 4430	2	103.4 1	上1排(支座1-支座2-N) 长:12770
	Φ25		4950	2	38.11	上1排(支座2)
	Φ22		3750	2	22.35	上2排(支座2)
	Φ25		3380	1	13.01	上1排(支座2-N右) 长:24400
	Φ25		2380	1	9.16	上1排(支座2-N右) 长:24400
	Φ12		5300	4	18.83	腰筋(1跨)
	Φ12		7900	8	56.12	腰筋(2跨)
	Φ12		3000	2	5.33	腰筋(3跨) 长:7810
	Φ12		2000	2	3.55	腰筋(3跨) 长:7810
	Φ25		5550	2	42.73	下1排(1跨)
	Φ25		8660	4	133.3 6	下1排(2跨)
	Φ25		3000	3	34.65	下2排(3跨) 长:8050
	Φ25		2000	3	23.10	下1排(3跨) 长:8050
	Φ8		2240	60	53.09	@100/200(2)1跨14+10+14+3,3跨14+5
	Φ8		2240	74	65.48	@100(2)2跨71+3

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ6		390	174	15.06	
61#WKL49 (2-M-2-N) 1 段	Φ25		4500 7000	2	88.55	上1排(支座2-M-支座2-N) 长:9000
	Φ25		7000 4500	2	88.55	上1排(支座2-M-支座2-N) 长:9000
	Φ22		4770	2	28.43	上1排(支座2-N左)
	Φ25		3400	2	26.18	上1排(支座2-N右) 长:24420
	Φ25		2400	2	18.48	上1排(支座2-N右) 长:24420
	Φ25		3300	3	38.11	上1排(支座2-N右)
	Φ12		8900	8	63.23	腰筋(1跨)
	Φ12		2800	4	9.95	腰筋(2跨) 长:7710
	Φ12		1800	4	6.39	腰筋(2跨) 长:7710
	Φ25		9000 660	4	148.7 6	下1排(1跨) 长:9000
	Φ25		3400	7	91.63	下2排(2跨) 长:8670
	Φ25		2400	7	64.68	下1排(2跨) 长:8670
	Φ10		2680	82	135.5 9	@100(4)1跨81+1
	Φ10		2240	82	113.3 3	1跨81+1
	Φ10		3280	27	54.64	@100(4)2跨26+1
	Φ10		2740	27	45.65	2跨26+1
	Φ8		580	156	35.74	
	Φ8		630	52	12.94	
62#L53 (2-L-2-N) 2 段 接8段	Φ25		9000 9000 4300	2	171.7 1	上1排(支座2-L左-支座2-N右)1,(支 座2-L左-支座2-N右)1 长:60770
	Φ25		5530	2	42.58	上1排(支座2-L)

审核:

翻样:






















构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		4280	2	32.96	上2排(支座2-L)
	Φ25		5050 9000	1	54.09	上1排(支座2-M左-支座2-N右) 长:14050
	Φ25		8300	1	31.95	上1排(支座6左-支座2-N右)
	Φ22		2350	3	21.01	上2排(支座6)
	Φ12		4100	2	7.28	腰筋(3跨) 长:7910 搭:190
	Φ12		3100	2	5.51	腰筋(3跨) 长:7910 搭:190
	Φ12		8350	8	59.32	腰筋(4跨)
	Φ12		8400	4	29.84	腰筋(5跨-6跨)
	Φ12		3000	2	5.33	腰筋(7跨) 长:7860
	Φ12		2000	2	3.55	腰筋(7跨) 长:7860
	Φ25		3150	2	24.25	下1排(3跨) 长:8150
	Φ25		4150	2	31.95	下1排(3跨) 长:8150
	Φ25		300 9000	2	71.61	下2排(4跨) 长:9300
	Φ25		8700	2	66.99	下1排(5跨-6跨)
	Φ25		4800	1	18.48	下1排(5跨)
	Φ25		3000	3	34.65	下2排(7跨) 长:8150
	Φ25		2000	3	23.10	下2排(7跨) 长:8150
	Φ8		2240	118	104.4 1	@100/200(2)3跨12+14+3,5跨 14+6+14,6跨14+4+14,7跨14+6+3
	Φ10		2280	54	75.97	@100/200(2)4跨14+23+14+3
	Φ6		390	140	12.12	
63#WKL46 (2-M-2-N)	Φ25		7500 2250	2	75.07	上1排(通长) 长:8150

审核:

翻样:



















第 64 页,共76页 2018/3/1 15:52

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
-1.00L	Φ25		3850	1	14.82	上1排(支座2-M右)
	Φ25		3260	2	25.10	上2排(支座2-M右)
	Φ25		3550	1	13.67	上1排(支座2-N左)
	Φ25		2960	3	34.19	上2排(支座2-N左)
	Φ12		7890	6	42.04	腰筋
	Φ22		8510	3	76.08	下1排
	Φ8		2040	76	61.24	@100(2)1跨71+5
	Φ6		340	102	7.70	
64#WKL46a (1-2-M)	Φ18		4030	3	24.18	上1排(通长)
-1.00L	Φ12		1380	2	2.45	腰筋
	Φ18		2260	3	13.56	下1排
	Φ8		1640	10	6.48	@100(2)1跨10
	Φ6		340	4	0.30	
6段人防：60~62为X向主梁、63~69为X向次梁 70~72为Y向梁 34*d 接8区梁						
6段右侧接8、甩11段-1.9~-1.0人防：（65~85为X向梁）						
65#L23 (2-8-2-8) 1段	Φ22		5200	1	15.50	上1排(支座2-8右) 长:57650
	Φ22		4200	1	12.52	上1排(支座2-8右) 长:57650
	Φ12		5000	4	17.76	腰筋(1跨) 长:9170
	Φ12		4000	4	14.21	腰筋(1跨) 长:9170
	Φ22		4000	2	23.84	下1排(1跨) 长:9460
	Φ22		5000	1	14.90	下1排(1跨) 长:9460

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		5000	1	19.25	下1排(1跨) 长:9570
	Φ25		4000	1	15.40	下1排(1跨) 长:9570
	Φ14		2670	2	6.46	(跨1)
	Φ8		2240	25	22.12	@150(2)1跨23+2
	Φ6		390	48	4.16	
66#L24 (2-8-2-8) 1段	Φ22		5200	1	15.50	上1排(支座2-8右) 长:57700
	Φ22		4200	1	12.52	上1排(支座2-8右) 长:57700
	Φ12		4500	3	11.99	腰筋(1跨) 长:8710
	Φ12		3500	3	9.32	腰筋(1跨) 长:8710
	Φ20		4500	4	44.46	下2排(1跨) 长:8850
	Φ20		3500	5	43.23	下1排(1跨) 长:8850
	Φ8		2240	33	29.20	@100/200(2)1跨14+16+3
	Φ6		390	36	3.12	
67#WKL4 (2-8-2-8) 1段	Φ25		5300	2	40.81	上1排(支座2-8右) 长:57720
	Φ25		4300	2	33.11	上1排(支座2-8右) 长:57720
	Φ14		4000	5	24.20	腰筋(1跨) 长:9210
	Φ14		5000	5	30.25	腰筋(1跨) 长:9210
	Φ25		5400	5	103.9 5	下2排(1跨) 长:9570
	Φ25		4400	6	101.6 4	下2排(1跨) 长:9570
	Φ16		3550	2	11.22	(跨1)
	Φ8		3340	46	60.69	@100(4)1跨45+1






















审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ8	 1150	2800	46	50.88	1跨45+1
	Φ8	 470	630	115	28.62	
68#L25 (2-8-2-8) 1段	Φ22	 4910	5200	1	15.50	上1排(支座2-8右) 长:57620
	Φ22	 3910	4200	1	12.52	上1排(支座2-8右) 长:57620
	Φ12	 4500	4500	3	11.99	腰筋(1跨) 长:8710
	Φ12	 3500	3500	3	9.32	腰筋(1跨) 长:8710
	Φ16	 4500	4500	1	7.11	下1排(1跨) 长:8750
	Φ16	 3500	3500	1	5.53	下1排(1跨) 长:8750
	Φ18	 4500	4500	1	9.00	下1排(1跨) 长:8800
	Φ18	 3500	3500	1	7.00	下1排(1跨) 长:8800
	Φ8	 800	2240	26	23.00	@200(2)1跨23+3
	Φ6	 270	390	36	3.12	
69#L4 (2-8-2-8) 1段	Φ25	 4970	5300	1	20.40	上1排(支座2-8右) 长:57700
	Φ25	 3970	4300	1	16.55	上1排(支座2-8右) 长:57700
	Φ12	 5000	5000	2	8.88	腰筋(1跨) 长:9010
	Φ12	 4000	4000	2	7.10	腰筋(1跨) 长:9010
	Φ25	 5000	5000	1	19.25	下1排(1跨) 长:9250
	Φ25	 4000	4000	2	30.80	下1排(1跨) 长:9250
	Φ8	 800	2240	33	29.20	@100/200(2)1跨14+16+3
	Φ6	 270	390	24	2.08	
70#WKL5 (2-8-2-8) 1段	Φ25	 4970	5300	2	40.81	上1排(支座2-8右)1,(支座2-8右)1 长:57720




















审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		4300	1	16.55	上1排(支座2-8右) 长:57720
	Φ25		3650	1	14.05	上1排(支座2-8右) 长:12320
	Φ25		3650	3	42.16	上1排(支座2-8右)
	Φ25		2950	7	79.50	上2排(支座2-8右)
	Φ12		5000	5	22.20	腰筋(1跨) 长:9260
	Φ12		4000	5	17.76	腰筋(1跨) 长:9260
	Φ25		5400	5	103.9 5	下1排(1跨) 长:9770
	Φ25		4400	6	101.6 4	下1排(1跨) 长:9770
	Φ10		3380	46	95.93	@100(4)1跨45+1
	Φ10		2840	46	80.60	1跨45+1
	Φ8		630	110	27.37	
71#L6 (2-8-2-8) 1段	Φ25		5300	1	20.40	上1排(支座2-8右) 长:57640
	Φ25		4300	1	16.55	上1排(支座2-8右) 长:57640
	Φ25		3300	1	12.70	上1排(支座2-8右) 长:11970
	Φ12		5000	2	8.88	腰筋(1跨) 长:9060
	Φ12		4000	2	7.10	腰筋(1跨) 长:9060
	Φ25		5000	2	38.50	下2排(1跨) 长:9300
	Φ25		4000	1	15.40	下2排(1跨) 长:9300
	Φ8		2240	33	29.20	@100/200(2)1跨14+16+3
	Φ6		390	24	2.08	
72#L9 (2-8-2-8) 1段	Φ25		5300	1	20.40	上1排(支座2-8右) 长:57640






















审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		3680	1	14.17	上1排(支座2-8右) 长:12348
	Φ25		4300	1	16.55	上1排(支座2-8右) 长:57640
	Φ12		5000	2	8.88	腰筋(1跨) 长:9060
	Φ12		4000	2	7.10	腰筋(1跨) 长:9060
	Φ25		5000	3	57.75	下2排(1跨) 长:9300
	Φ25		4000	4	61.60	下2排(1跨) 长:9300
	Φ8		2240	38	33.62	@100/150(2)1跨14+22+2
	Φ6		390	32	2.77	
73#WKL7 (8-8) 1段	Φ25		5300	2	40.81	上1排(支座8右)1,(支座8右)1 长:57800
	Φ25		3650	1	14.05	上1排(支座8右) 长:12320
	Φ25		4300	1	16.55	上1排(支座8右) 长:57800
	Φ25		3650	3	42.16	上1排(支座8右)
	Φ25		2950	7	79.50	上2排(支座8右)
	Φ12		4000	5	17.76	腰筋(1跨) 长:9260
	Φ12		5000	5	22.20	腰筋(1跨) 长:9260
	Φ25		4400	2	33.88	下2排(1跨) 长:9770
	Φ25		5400	1	20.79	下2排(1跨) 长:9770
	Φ10		3380	47	98.02	@100(4)1跨45+2
	Φ10		2840	47	82.36	1跨45+2
	Φ8		630	115	28.62	
74#L12 (8-8) 1段	Φ25		2000	2	15.40	上1排(支座8右)1,(支座8右)1 长:46720

审核:






















翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		3000	2	23.10	上1排(支座8右)1,(支座8右)1 长:17570
	Φ12		2680	2	4.76	腰筋(1跨) 长:6990
	Φ12		1680	2	2.98	腰筋(1跨) 长:6990
	Φ25		2750	3	31.76	下1排(1跨) 长:7250
	Φ25		1750	3	20.21	下1排(1跨) 长:7250
	Φ8		2140	18	15.22	@100/200(4)1跨11+7
	Φ8		1740	18	12.37	1跨11+7
	Φ8		530	14	2.93	
75#WKL8 (8/10-1/2-10)	Φ25		7250	2	55.82	上1排(通长)
	Φ25		2700	1	10.39	上1排(支座1/2-10左)
	Φ25		2300	2	17.71	上2排(支座1/2-10左)
	Φ12		4900	2	8.70	腰筋
	Φ25		6100	3	70.45	下1排
	Φ8		1640	45	29.15	@100(2)1跨45
	Φ6		340	22	1.66	
16#WKL9 (1/2-10-1/2-10) 1段	Φ25		5300	1	20.40	上1排(支座1/2-10右) 长:39659
	Φ25		4300	1	16.55	上1排(支座1/2-10右) 长:39659
	Φ25		3570	2	27.49	上1排(支座1/2-10右)
	Φ12		4500	2	7.99	腰筋(1跨) 长:7660
	Φ12		3500	2	6.22	腰筋(1跨) 长:7660
	Φ25		3800	3	43.89	下2排(1跨) 长:8470

审核:

翻样:


















第 70 页,共76页 2018/3/1 15:52





















构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		4800	3	55.44	下1排(1跨) 长:8470
	Φ8		2240	32	28.31	@100(2)1跨31+1
	Φ6		390	32	2.77	
//WKL11 (1/2-10-1/2-10) 1段	Φ25		5100	1	19.63	上1排(支座1/2-10右) 长:49270
	Φ25		4100	1	15.78	上1排(支座1/2-10右) 长:49270
	Φ25		5080	1	19.56	上1排(支座1/2-10右) 长:49270
	Φ25		3350	4	51.59	上1排(支座1/2-10右)
	Φ25		2750	5	52.94	上2排(支座1/2-10右)
	Φ12		4500	4	15.98	腰筋(1跨) 长:7610
	Φ12		3500	4	12.43	腰筋(1跨) 长:7640
	Φ25		4000	5	77.00	下2排(1跨) 长:8700
	Φ25		5000	6	115.50	下1排(1跨) 长:8670
	Φ18		3500	2	14.00	(跨1)
	Φ10		3280	33	66.78	@100(4)1跨32+1
	Φ10		2740	33	55.79	1跨32+1
	Φ8		630	64	15.93	
/8#WKL11a (1/2-10-1/2-10) 1段	Φ25		4500	1	17.32	上1排(支座1/2-10右) 长:8250
	Φ25		5500	1	21.17	上1排(支座1/2-10右) 长:8250
	Φ25		3820	3	44.12	上1排(支座1/2-10右)
	Φ25		3210	5	61.79	上2排(支座1/2-10右)
	Φ25		3210	4	49.43	上3排(支座1/2-10右)

审核:

翻样:






















构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ12		4500	2	7.99	腰筋 长:7660
	Φ12		3500	2	6.22	腰筋 长:7660
	Φ25		5000	3	57.75	下1排 长:8240
	Φ25		4000	3	46.20	下1排 长:8240
	Φ10		2380	25	36.71	@100/200(4)1跨13+9+3
	Φ10		1980	25	30.54	1跨13+9+3
	Φ8		530	16	3.35	
79#L15 (8-10)	Φ22		2800	2	16.69	上1排(通长)
-1.00L	Φ12		2310	2	4.10	腰筋
	Φ22		2800	2	16.69	下1排
	Φ8		1640	15	9.72	@100(2)1跨15
	Φ6		340	7	0.53	
80#WKL15 (1/2-10-1/2-10) 1段	Φ25		5400	2	41.58	上1排(支座1/2-10右)1,(支座1/2-10右)1 长:48900
	Φ25		4350	1	16.75	上1排(支座1/2-10右) 长:48900
	Φ25		3750	2	28.87	上1排(支座1/2-10右)
	Φ12		5000	5	22.20	腰筋(1跨) 长:8060
	Φ12		4000	5	17.76	腰筋(1跨) 长:8060
	Φ25		4000	2	30.80	下2排(1跨) 长:8570
	Φ25		4000	8	123.20	下1排(1跨)
	Φ16		3430	2	10.84	(跨1)
	Φ8		3240	33	42.23	@100(4)1跨32+1

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ8	 1100	2700	33	35.19	1跨32+1
	Φ8	 470	630	80	19.91	
81#L15 (2-8-2)	Φ22	330  330	2800	2	16.69	上1排(通长)
-1.00L	Φ12	180  180	2540	2	4.51	腰筋
	Φ22	330  330	2800	2	16.69	下1排
	Φ8	 350	1140	22	9.91	@80(2)1跨22
	Φ6	 170	290	10	0.64	
82#L20 (1-1/2-10)	Φ22	330  330	7600	2	45.30	上1排(通长)
-1.00L	Φ12	 6900	6900	2	12.25	腰筋(通长)
	Φ25	200  4150	4300	2	33.11	下1排(1跨)
	Φ25	 3200	3200	2	24.64	下1排(2跨)
	Φ8	 550	1640	50	32.39	@100/200(2)1跨10+8+10,2跨10+2+10
	Φ6	 220	340	14	1.06	
83#WKL15 (2-8-1/2-10)	Φ25	850  850 套	8360 2390	2	82.77	上1排(通长) 长:9150
-1.00L	Φ25	850  3130	3930	1	15.13	上1排(支座2-8右)
	Φ25	 3180 850	3980	2	30.65	上1排(支座1/2-10左)
	Φ22	 2480 750	3190	4	38.02	上2排(支座1/2-10左)
	Φ12	180  8840 970 180 搭	9000 970	8	70.83	腰筋 长:9220 搭:590
	Φ22	330  8710 440 330 套	9000 730	3	86.99	下2排 长:9150
	Φ22	330  8710 440 330 套	9000 730	5	144.9 8	下1排 长:9150
	Φ10	 800	2280	70	98.47	@100/150(2)1跨14+38+14+4

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ6		390	112	9.70	
84#L26 (8-1/2-10)	Φ25		7690	3	88.82	上1排(通长)
-1.00L	Φ12		6900	2	12.25	腰筋
	Φ22		7120	4	84.87	下1排
	Φ8		1640	66	42.75	@100(2)1跨65+1
	Φ6		340	32	2.42	
85#L22 (2-8-2)	Φ22		2800	2	16.69	上1排(通长)
	Φ22		2800	2	16.69	上2排(通长)
	Φ22		2400	2	14.30	下1排
	Φ8		1140	22	9.91	@80(2)1跨22
6段右下侧接8、非人防~人防（86~87为Y向梁）						
86#WKL44 (2-K-2)	Φ25		6050	2	46.58	上1排(通长)
	Φ25		2450	2	18.86	上1排(支座2-K右)
	Φ25		2450	3	28.30	上1排(支座2左)
	Φ12		1650	2	2.93	架立筋
	Φ12		4510	8	32.04	腰筋
	Φ22		5160	4	61.51	下1排
	Φ8		2440	38	36.62	@100(4)1跨37+1
	Φ8		2040	38	30.62	1跨37+1
	Φ8		530	72	15.07	
87#WKL47 (1-2-K)	Φ25		9000 4700	2	105.4 9	上1排(通长) 长:12150






审核：

翻样：

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ25		7490	2	57.67	上1排(支座1-支座2-J右)
	Φ25		6850	2	52.74	上2排(支座1-支座2-J右)
	Φ25		1900	1	7.31	上2排(支座1右)
	Φ25		3700	1	14.24	上1排(支座2-K左)
	Φ12		3900	4	13.85	腰筋(1跨)
	Φ12		7900	4	28.06	腰筋(2跨)
	Φ22		4790	3	42.82	下1排(1跨)
	Φ22		9000	2	53.64	下2排(2跨)
	Φ22		9000	5	134.10	下1排(2跨)
	Φ16		2750	2	8.69	(跨1)
	Φ8		2240	36	31.85	@100(2)1跨35+1
	Φ8		2240	57	50.43	@100/200(2)2跨14+23+14+6
	Φ6		390	70	6.06	
88#L50 (2-H-3) 2段	Φ20		8960	3	66.39	上1排(支座2-H左-支座3) 长:12940
	Φ20		9000 960	2	49.20	上1排(支座2-H左-支座3) 长:12940
	Φ20		1410	5	17.41	上2排(支座3左)
	Φ12		4620	3	12.31	腰筋(1跨) 长:8630 搭:190
	Φ12		5620	3	14.97	腰筋(1跨) 长:8630 搭:190
	Φ12		4100	6	21.84	腰筋(2跨)
	Φ20		4570	4	45.15	下2排(1跨) 长:8770
	Φ20		5570	5	68.79	下1排(1跨) 长:8770

审核:

翻样:

构件名称	级直 别径	钢 筋 简 图	下料 (mm)	根 件 数*数	重量 (kg)	备 注
	Φ20		4300	3	31.86	下1排(2跨)
	Φ16		2750	2	8.69	(跨2)
	Φ8		2240	36	31.85	@100/200(2)1跨19+14+3
	Φ8		2240	38	33.62	@100(2)2跨37+1
	Φ6		390	90	7.79	