

料表编号:

- 绑扎
- 配料
- 留存

# 恒坪房地产开发有限公司

项目: 恒大, 深林海

栋号: 6#楼

部位: 基础\_梁配筋

相同层数: 1

序号	分类	Φ8	Φ10	Φ12	Φ14	Φ18	Φ22	Φ25	Φ28	合计
1	重量	1123	11179	5836	2551	52	18636	3298	4471	47.146
2	套筒							28	11	39
3	电焊						28			28
4	电渣焊						142			142
5	搭接				76					76

注:重量单位明细为公斤、合计为吨;接头单位为个。

混凝土

C40

锚固 $L_a$

$d \leq 25 = 29d, d > 25 = 32d$

加筋与通长筋搭接 $L_i$   $d \leq 25 = 41d, d > 25 = 45d$

加筋替代CTL通长筋

直径较大钢筋与直径较小钢筋搭接时,以直径较小钢筋计算长度

腰筋搭接 $15d$ ,排布与防水板以上500范围

梁绑扎时,按小图编号依次绑扎

日期: 2018年04月23日



# 钢筋配料表

3级C30锚固32, 31, 37, 45

栋号: 6#楼
























部位: 基础\_梁配筋

构件名称	级直别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备注
CTL-1 (1-#)	Φ22		8350	6	6	149.30	上1排(通长)
	Φ14		8000	4	4	38.72	腰筋
	Φ22		8350	6	6	149.30	下1排
	Φ10		3860	41	41	97.65	@200(6)1跨41
	Φ10		2460	82	82	124.46	1跨82
	Φ8		1100	40	40	17.38	
CTL-1 (2-#)	Φ22		3580	6	6	64.01	上1排(1跨)
	Φ28		4350	8	8	168.08	洞口上部加筋
	Φ22		4100	6	6	73.31	上1排(2跨)
	Φ25		4300	8	8	132.44	洞口上部加筋
	Φ22		7130	6	6	127.48	上1排(3跨)
	Φ14		9000 9000 1820	4	4	95.93	腰筋(通长) 长:19400 搭:210
	Φ22		9000 9000 2020	6	6	357.96	下1排(通长) 长:19400 单:220
	Φ10		3860	74	74	176.24	@200(6)1跨18,2跨21,3跨35
	Φ10		2460	148	148	224.64	1跨36,2跨42,3跨70
	Φ12		3900	48	48	166.23	洞口,@100
	Φ12		2660	96	96	226.76	洞口,@100
	Φ8		1100	118	118	51.27	
	CTL-1 (3-#)	Φ22		4280	6	6	76.53
Φ25			3950	7	7	106.45	南洞口上部加筋
Φ22			3850	6	6	68.84	上1排(2跨)

审核:

翻样: 钟祥祯13653434429
























第 1 页,共22页

构件名称	级直 别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备注
	Φ25		4300	8	8	132.44	北洞口上部加筋
	Φ22		7080	6	6	126.59	上1排(3跨)
	Φ14		9000 9000 1820	4	4	95.93	腰筋(通长) 长:19400 搭:210
	Φ22		9000 9000 2020	6	6	357.96	下1排(通长) 长:19400 单:220
	Φ10		3860	76	76	181.00	@200(6)1跨21,2跨20,3跨35
	Φ10		2460	152	152	230.71	1跨42,2跨40,3跨70
	Φ12		3900	24	24	83.12	北洞口,@100
	Φ12		2660	48	48	113.38	北洞口,@100
	Φ12		3900	20	20	69.26	南洞口,@100
	Φ12		2460	40	40	87.38	南洞口,@100
	Φ8		1100	118	118	51.27	
CTL-1 (4-#)	Φ22		4680	6	6	83.68	上1排(1跨)
	Φ28		4350	8	8	168.08	洞口上部加筋
	Φ22		4280	6	6	76.53	上1排(2跨)
	Φ14		9000 2310	4	4	54.74	腰筋(通长) 长:11100 搭:210
	Φ22		9000 2500	6	6	205.62	下1排(通长) 长:11100 单:220
	Φ10		3860	44	44	104.79	@200(6)1跨23,2跨21
	Φ10		2460	88	88	133.57	1跨46,2跨42
	Φ12		3900	24	24	83.12	洞口,@100
	Φ12		2660	48	48	113.38	洞口,@100
	Φ8		1100	66	66	28.68	
CTL-2 (5-#)	Φ22		9000 2500	7	7	239.89	上1排(通长) 长:11100 单:220
	Φ14		9000 2310	4	4	54.74	腰筋 长:11100 搭:210

审核:

翻样: 钟祥祯13653434429
























第 2 页,共22页
























构件名称	级直别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备注
	Φ22		9000 2500	7	7	239.89	下1排 长:11100 单:220
	Φ10		4260	56	56	147.19	@200(7)1跨56
	Φ10		2460	112	112	170.00	1跨112
	Φ10		1120	56	56	38.70	1跨56
	Φ8		1100	54	54	23.46	
CTL-1 (6-#)	Φ22		4030	6	6	72.06	上1排(1跨)
	Φ28		2950	8	8	113.99	洞口上部加筋
	Φ22		3630	6	6	64.90	上1排(2跨)
	Φ14		8400	4	4	40.66	腰筋(通长)
	Φ22		8750	6	6	156.45	下1排(通长)
	Φ10		3860	38	38	90.50	@200(6)1跨20,2跨18
	Φ10		2460	76	76	115.35	1跨40,2跨36
	Φ12		3900	10	10	34.63	洞口,@100
	Φ12		2660	20	20	47.24	洞口,@100
	Φ8		1100	44	44	19.12	
CTL-1 (7-#)	Φ22		3930	6	6	70.27	上1排(1跨)
	Φ25		3350	7	7	90.28	洞口上部加筋
	Φ22		9000 3470	3	3	111.48	上1排(2跨) 长:12250 单:220
	Φ22		3470 9000	3	3	111.48	上1排(2跨) 长:12250 单:220
	Φ14		4000 9000 4940	2	2	43.41	腰筋(通长) 长:17500 搭:220
	Φ14		5000 9000 3940	2	2	43.41	腰筋(通长) 长:17500 搭:220
	Φ22		3930	6	6	70.27	下1排(支座7-支座2)3,(支 座7-支座2)3
	Φ28		3350	8	8	129.44	洞口下部加筋

审核:

翻样: 钟祥祯13653434429

第 3 页,共22页
























构件名称	级直别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备注
	Φ22		9000 3470	3	3	111.48	下1排(支座2-支座#) 长:12250 单:220
	Φ22		3470 9000	3	3	111.48	下1排(支座2-支座#) 长:12250 单:220
	Φ10		3860	82	82	195.29	@200(6)1跨20,2跨62
	Φ10		2460	164	164	248.92	1跨40,2跨124
	Φ12		3900	14	14	48.48	洞口,@100
	Φ12		2460	28	28	61.17	洞口,@100
	Φ8		1100	92	92	39.97	
CTL-1 (8-#)	Φ22		2730	6	6	48.81	上1排(1跨)
	Φ28		9000 250	11	11	491.45	洞口上部加筋
	Φ22		2730	6	6	48.81	上1排(2跨)
	Φ14		9000 3720	4	4	61.56	腰筋(通长) 长:12500 搭:220
	Φ22		2730	6	6	48.81	下1排(支座8-支座2)
	Φ25		9000 250	8	8	284.90	洞口下部加筋
	Φ22		2730	6	6	48.81	下1排(支座2-支座#)
	Φ10		3860	26	26	61.92	@200(6)1跨13,2跨13
	Φ10		2460	52	52	78.93	1跨26,2跨26
	Φ12		3900	73	73	252.81	洞口,@100
	Φ12		2500	146	146	324.12	洞口,@100
	Φ8		1100	96	96	41.71	
	CTL-1 (9-#)	Φ22		3080	6	6	55.07
Φ25			8550	8	8	263.34	洞口上部加筋
Φ22			3080	6	6	55.07	上1排(2跨)
Φ14			9000 3720	4	4	61.56	腰筋(通长) 长:12500 搭:220
























构件名称	级直 别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备注
	Φ22	220  2900	3080	6	6	55.07	下1排(支座9-支座2)
	Φ28	 8550	8550	10	10	412.96	洞口下部加筋
	Φ22	 2900 220	3080	6	6	55.07	下1排(支座2-支座#)
	Φ10	 920 920	3860	30	30	71.45	@200(6)1跨15,2跨15
	Φ10	 220 920	2460	60	60	91.07	1跨30,2跨30
	Φ12	 920 920	3900	66	66	228.57	洞口,@100
	Φ12	 300 920	2660	132	132	311.79	洞口,@100
	Φ8	 940	1100	92	92	39.97	
CTL-1 (10-#)	Φ22	220  3750	3930	6	6	70.27	上1排(1跨)
	Φ25	 3350	3350	7	7	90.28	洞口上部加筋
	Φ22	 9000 3290 对 220	9000 3470	3	3	111.48	上1排(2跨) 长:12250 对:40
	Φ22	 3470 8820 对 220	3470 9000	3	3	111.48	上1排(2跨) 长:12250 对:40
	Φ14	 3000 9000 5940 搭 搭	3000 9000 5940	4	4	86.83	腰筋(通长) 长:17500 搭:220
	Φ22	220  3750	3930	6	6	70.27	下1排(支座10-支座2)
	Φ28	 3350	3350	8	8	129.44	洞口下部加筋
	Φ22	 9000 3290 220 对	9000 3470	3	3	111.48	下1排(支座2-支座#) 长:12250 对:40
	Φ22	 3470 8820 220 对	3470 9000	3	3	111.48	下1排(支座2-支座#) 长:12250 对:40
	Φ10	 920 920	3860	82	82	195.29	@200(6)1跨20,2跨62
	Φ10	 220 920	2460	164	164	248.92	1跨40,2跨124
	Φ12	 920 920	3900	14	14	48.48	洞口,@100
	Φ12	 200 920	2460	28	28	61.17	洞口,@100
	Φ8	 940	1100	92	92	39.97	
CTL-1 (11-#)	Φ22	220  3850	4030	6	6	72.06	上1排(1跨)

审核:
























翻样: 钟祥祯13653434429
























第 5 页,共22页

构件名称	级直别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备注
	Φ28		2950	8	8	113.99	洞口上部加筋
	Φ22		3630	6	6	64.90	上1排(2跨)
	Φ14		8400	4	4	40.66	腰筋(通长)
	Φ22		8750	6	6	156.45	下1排(通长)
	Φ10		3860	38	38	90.50	@200(6)1跨20,2跨18
	Φ10		2460	76	76	115.35	1跨40,2跨36
	Φ12		3900	10	10	34.63	洞口,@100
	Φ12		2660	20	20	47.24	洞口,@100
	Φ8		1100	44	44	19.12	
CTL-1 (12-#)	Φ22		8750	6	6	156.45	上1排(通长)
	Φ14		8400	4	4	40.66	腰筋
	Φ22		8750	6	6	156.45	下1排
	Φ10		3860	43	43	102.41	@200(6)1跨43
	Φ10		2460	86	86	130.53	1跨86
	Φ8		1100	42	42	18.25	
CTL-1 (13-#)	Φ22		7720	6	6	138.03	上1排(通长)
	Φ14		6710	4	4	32.48	腰筋
	Φ22		7720	6	6	138.03	下1排
	Φ10		3860	33	33	78.59	@200(6)1跨33
	Φ10		2460	66	66	100.18	1跨66
	Φ8		1100	32	32	13.90	
CTL-1 (14-#)	Φ22		5400	6	6	96.55	上1排(通长)
	Φ14		4400	4	4	21.30	腰筋

构件名称	级直别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备注
	Φ22	220  2930	3110	6	6	55.61	下1排
	Φ25	 3080 250	3280	7	7	88.40	洞口下部加筋
	Φ10	 920 920	3860	11	11	26.20	@200(6)1跨11
	Φ10	 220 920	2460	22	22	33.39	1跨22
	Φ12	 920 920	3900	21	21	72.73	洞口,@100
	Φ12	 220 920	2500	42	42	93.24	洞口,@100
	Φ8	 940	1100	28	28	12.17	
CTL-1 (15-#)	Φ22	220  5050 220	5400	6	6	96.55	上1排(通长)
	Φ14	 4400	4400	4	4	21.30	腰筋
	Φ22	220  5050 220	5400	6	6	96.55	下1排
	Φ10	 920 920	3860	21	21	50.01	@200(6)1跨21
	Φ10	 220 920	2460	42	42	63.75	1跨42
	Φ8	 940	1100	20	20	8.69	
CTL-1 (16-#)	Φ22	220  7240 220	7590	6	6	135.71	上1排(通长)
	Φ14	 5900	5900	4	4	28.56	腰筋(通长)
	Φ22	220  7240 220	7590	6	6	135.71	下1排(通长)
	Φ10	 920 920	3860	24	24	57.16	@200(6)1跨14,2跨10
	Φ10	 220 920	2460	48	48	72.86	1跨28,2跨20
	Φ8	 940	1100	20	20	8.69	
CTL-1 (17-#)	Φ22	220  4440 220	4790	6	6	85.65	上1排(通长)
	Φ14	 3100	3100	4	4	15.00	腰筋
	Φ22	220  4440 220	4790	6	6	85.65	下1排
	Φ10	 920 920	3860	14	14	33.34	@200(6)1跨14


























构件名称	级直 别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备注
	Φ10	 920	2460	28	28	42.50	1跨28
	Φ8	 940	1100	12	12	5.21	
CTL-1 (18-#)	Φ22	220  4130	4310	6	6	77.06	上1排(1跨)
	Φ25	 4880	4880	6	6	112.73	洞口上部加筋
	Φ22	 1420	1600	6	6	28.61	上1排(2跨)
	Φ14	 7200	7200	4	4	34.85	腰筋(通长)
	Φ22	220  8510	8860	6	6	158.42	下1排(通长)
	Φ10	 920	3860	20	20	47.63	@200(6)1跨17,2跨3
	Φ10	 920	2460	40	40	60.71	1跨34,2跨6
	Φ12	 920	3900	30	30	103.90	洞口,@100
	Φ12	 920	2500	60	60	133.20	洞口,@100
	Φ8	 940	1100	44	44	19.12	
CTL-1 (19-#)	Φ22	220  7760	8110	6	6	145.01	上1排(通长)
	Φ14	 7100	7100	4	4	34.36	腰筋
	Φ22	220  7760	8110	6	6	145.01	下1排
	Φ10	 920	3860	35	35	83.36	@200(6)1跨35
	Φ10	 920	2460	70	70	106.25	1跨70
	Φ8	 940	1100	34	34	14.77	
CTL-1 (20-#)	Φ22	220  4540	4890	6*2	12	174.87	上1排(通长)
	Φ14	 3200	3200	4*2	8	30.98	腰筋
	Φ22	220  4540	4890	6*2	12	174.87	下1排
	Φ10	 920	3860	14*2	28	66.69	@200(6)1跨14
	Φ10	 920	2460	28*2	56	85.00	1跨28

构件名称	级直别径	钢筋简图	下料(mm)	根件数*数	总根数	重量(kg)	备注
	Φ8		1100	12*2	24	10.43	
CTL-1 (21-#)	Φ22		3510	6	6	62.76	上1排(通长)
	Φ14		2500	4	4	12.10	腰筋
	Φ22		3510	6	6	62.76	下1排
	Φ10		3860	12	12	28.58	@200(6)1跨12
	Φ10		2460	24	24	36.43	1跨24
	Φ8		1100	10	10	4.35	
CTL-1 (22-#)	Φ28		3670	8	8	141.81	上部洞口加筋(1跨)
	Φ22		9000 6240	6	6	272.49	上1排(2跨) 长:15200 对:40
	Φ28		3670	8	8	141.81	上部洞口加筋(3跨)
	Φ14		9000 9000 1350	4	4	93.65	腰筋(通长) 长:18910 搭:220
	Φ22		9000 9000 2860	6	6	372.98	下1排(通长) 长:20240 单:220,对:40
	Φ10		3860	77	77	183.38	@200(6)2跨77
	Φ10		2460	154	154	233.74	2跨154
	Φ12		3900	30	30	103.90	洞口,@100
	Φ12		2500	60	60	133.20	洞口,@100
	Φ8		1100	104	104	45.19	
CTL-1 (23-#)	Φ22		9000 4900	6	6	248.53	上1排(通长) 长:13500 对:40
	Φ14		9000 4720	4	4	66.40	腰筋 长:13500 搭:220
	Φ22		9000 4900	6	6	248.53	下1排 长:13500 对:40
	Φ10		3860	69	69	164.33	@200(6)1跨69
	Φ10		2460	138	138	209.46	1跨138
	Φ8		1100	66	66	28.68	

审核:

翻样: 钟祥祯13653434429

第 9 页,共22页
























构件名称	级直别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备注
CTL-1 (24-#)	Φ22		7470	6	6	133.56	上1排(通长)
	Φ14		7120	4	4	34.46	腰筋
	Φ28		3340	11	11	177.45	下部洞口加筋(1跨)
	Φ22		5100	6	6	91.19	下1排
	Φ10	 920	3860	29	29	69.07	@200(6)1跨26
	Φ10	 920	2460	58	58	88.03	1跨52
	Φ12	 920	3900	17	17	58.87	洞口,@100
	Φ12	 920	2500	34	34	75.48	洞口,@100
	Φ8		1100	37	37	16.08	
CTL-1 (25-#)	Φ22		3300	6	6	59.00	上1排(通长)
	Φ14		2950	4	4	14.28	腰筋
	Φ22		3300	6	6	59.00	下1排
	Φ10	 920	3860	16	16	38.11	@200(6)1跨16
	Φ10	 920	2460	32	32	48.57	1跨32
	Φ8		1100	14	14	6.08	
CTL-1 (26-#)	Φ22		7870	6	6	140.72	上1排(通长)
	Φ14		7520	4	4	36.40	腰筋
	Φ28		3340	11	11	177.45	下部洞口加筋(1跨)
	Φ22		5500	6	6	98.34	下1排
	Φ10	 920	3860	31	31	73.83	@200(6)1跨28
	Φ10	 920	2460	62	62	94.10	1跨56
	Φ12	 920	3900	17	17	58.87	洞口,@100
	Φ12	 920	2500	34	34	75.48	洞口,@100
























构件名称	级直别径	钢筋简图	下料(mm)	根件数*数	总根数	重量(kg)	备注
	Φ8		1100	46	46	19.99	
CTL-1 (27-#)	Φ22		3700	6	6	66.16	上1排(通长)
	Φ14		3350	4	4	16.21	腰筋
	Φ22		3700	6	6	66.16	下1排
	Φ10		3860	18	18	42.87	@200(6)1跨18
	Φ10		2460	36	36	54.64	1跨36
	Φ8		1100	16	16	6.95	
CTL-1 (28#-30#)	Φ22		3430	6	6	61.33	上1排(1跨)
	Φ28		3950	9	9	171.71	28#洞口加筋,上1排
	Φ28		4020	3	3	58.25	28#洞口加筋,上1排
	Φ28		3950	3	3	57.24	28#洞口加筋,上2排
	Φ28		4020	1	1	19.42	28#洞口加筋,上2排
	Φ22		9000 690	5	5	144.38	上1排(2跨) 长:9650 对:40
	Φ28		5300	8	8	204.79	30#洞口加筋,上1排
	Φ28		5420	3	3	78.54	30#洞口加筋,上1排
	Φ22		2030	6	6	36.30	上1排(3跨)
	Φ14		9000 9000 1310	2	2	46.73	腰筋(通长) 长:18870 搭:220
	Φ14		8450	2	2	20.45	腰筋(2跨)
	Φ14		4750	4	4	22.99	腰筋(1跨)2,(3跨)2
	Φ22		6450	2	2	38.44	下1排(28#)1,(30#)1
	Φ22		9000 9000 2860	5	5	310.81	下1排(通长)5长:20240 单:220,对:40
	Φ10		3860	14	14	33.34	@200(6)1跨12,3跨5
	Φ10		2460	28	28	42.50	1跨24,3跨10
























审核:
























翻样: 钟祥祯13653434429

第 11 页,共22页
























构件名称	级直别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备注
	Φ10	 920	3260	41	41	82.47	@200(4)29#41
	Φ10	 920	2680	41	41	67.80	29#41
	Φ12	 920	3900	37	37	128.14	洞口,@100,28#15,30#22
	Φ12	 920	2500	74	74	164.28	洞口,@100,28#15,30#22
	Φ8	 640	800	46	46	14.54	
	Φ8	 940	1100	62	62	26.94	
CTL-1 (31-#)	Φ25	250  2900	3100	8*2	16	190.96	上部洞口加筋
	Φ22	 4450 220	4630	6*2	12	165.57	上1排(通长)
	Φ14	 4900	4900	4*2	8	47.43	腰筋
	Φ25	250  2900	3100	6*2	12	143.22	下部洞口加筋
	Φ22	 4450 220	4630	6*2	12	165.57	下1排
	Φ10	 920	3860	18*2	36	85.74	@200(6)1跨18
	Φ10	 920	2460	36*2	72	109.28	1跨36
	Φ12	 920	3900	8*2	16	55.41	洞口,@100
	Φ12	 920	2660	16*2	32	75.59	洞口,@100
	Φ8	 940	1100	24*2	48	20.86	
CTL-1 (32-#)	Φ22	220  5940 220	6290	6*2	12	224.93	上1排(通长)
	Φ14	 4600	4600	4*2	8	44.53	腰筋
	Φ22	220  2950	3130	6*2	12	111.93	下1排
	Φ28	 4000 280	4220	8*2	16	326.12	下部洞口加筋
	Φ10	 920	3860	10*2	20	47.63	@200(6)1跨10
	Φ10	 920	2460	20*2	40	60.71	1跨20
	Φ12	 920	3900	21*2	42	145.45	洞口,@100
























构件名称	级直别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备注
	Φ12	 920	2500	42*2	84	186.48	洞口,@100
	Φ8	 940	1100	29*2	58	25.20	
CTL-1 (33-#)	Φ22	220  4200	4380	6*2	12	156.63	上1排(通长)
	Φ28	 3500 280	3720	8*2	16	287.48	上部洞口加筋
	Φ14	 5350	5350	4*2	8	51.79	腰筋
	Φ22	220  4200	4380	6*2	12	156.63	下1排
	Φ25	 3500 250	3700	7*2	14	199.43	下部洞口加筋
	Φ10	 920 920	3860	17*2	34	80.98	@200(6)1跨17
	Φ10	 920 220	2460	34*2	68	103.21	1跨34
	Φ12	 920 920	3900	15*2	30	103.90	洞口,@100
	Φ12	 920 300	2660	30*2	60	141.72	洞口,@100
	Φ8	 940	1100	29*2	58	25.20	
CTL-1 (34-#)	Φ22	220  8820 4660 对 220	9000 4840	6	6	247.46	上1排(通长) 长:13440 对:40
	Φ14	 9000 3320 搭	9000 3320	4	4	59.63	腰筋 长:12100 搭:220
	Φ22	220  8820 4660 对 220	9000 4840	6	6	247.46	下1排 长:13440 对:40
	Φ10	 920 920	3860	49	49	116.70	@200(6)1跨49
	Φ10	 920 220	2460	118	118	179.10	1跨118
	Φ8	 940	1100	56	56	24.33	
	加腋钢筋	Φ18	 2600	2600	5*2	10	52.00
Φ10		 920 1120~1920	4260 ~5860	5*2	10	31.22	下料长度△400mm,箍筋 宽度△200mm@200(6)1跨5
CTL-1 (35-#)	Φ22	220  4200	4380	6	6	78.31	上1排(1跨)
	Φ28	 3950	3950	8	8	152.63	上部洞口加筋
	Φ22	 3800 220	3980	6	6	71.16	上1排(2跨)
























构件名称	级直别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备注
	Φ14		8700	4	4	42.11	腰筋(通长)
	Φ22		4380	6	6	78.31	下1排(支座33-支座2)
	Φ25		3950	7	7	106.45	下部洞口加筋
	Φ22		3980	6	6	71.16	下1排(支座2-支座#)
	Φ10		3860	29	29	69.07	@200(6)1跨17,2跨12
	Φ10		2460	58	58	88.03	1跨34,2跨24
	Φ12		3900	16	16	55.41	洞口,@100
	Φ12		2660	32	32	75.59	洞口,@100
	Φ8		1100	40	40	17.38	
CTL-3a (36-#)	Φ25		9000 900	5	5	190.57	上1排(通长) 长:9500
	Φ14		9500	4	4	45.98	腰筋
	Φ25		4500 5400	5	5	190.57	下1排 长:9500
	Φ10		3060	48	48	90.62	@200(4)1跨48
	Φ10		2620	48	48	77.59	1跨48
	Φ8		700	46	46	12.72	
CTL-3 (37-#)	Φ22		3540	4*2	8	84.39	上1排(通长)
	Φ14		2550	4*2	8	24.68	腰筋
	Φ22		3540	4*2	8	84.39	下1排
	Φ10		3060	11*2	22	41.54	@200(4)1跨11
	Φ10		2420	11*2	22	32.85	1跨11
	Φ8		700	8*2	16	4.42	
CTL-1 (38-#)	Φ22		9000 7090	6	6	287.69	上1排(通长) 长:15690 对:40
	Φ14		9000 5570	4	4	70.52	腰筋(通长) 长:14350 搭:220
























构件名称	级直别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备注
	Φ22		9000 7090	6	6	287.69	下1排(通长) 长:15690 对:40
	Φ10		3860	56	56	133.37	@200(6)1跨15,2跨14,3跨13,4跨14
	Φ10		2460	112	112	170.00	1跨30,2跨28,3跨26,4跨28
	Φ8		1100	48	48	20.86	
CTL-1 (39-#)	Φ22		6620	6	6	118.37	上1排(通长)
	Φ14		6270	4	4	30.35	腰筋
	Φ22		6620	6	6	118.37	下1排
	Φ10		3860	28	28	66.69	@200(6)1跨28
	Φ10		2460	56	56	85.00	1跨56
	Φ8		1100	26	26	11.30	
CTL-1 (40-#)	Φ22		6090	6*2	12	217.78	上1排(通长)
	Φ14		4400	4*2	8	42.59	腰筋
	Φ22		6090	6*2	12	217.78	下1排
	Φ10		3860	20*2	40	95.26	@200(6)1跨20
	Φ10		2460	40*2	80	121.43	1跨40
	Φ8		1100	18*2	36	15.64	
CTL-1 (41-#)	Φ22		6520	6	6	116.58	上1排(通长)
	Φ14		5500	4	4	26.62	腰筋
	Φ22		6520	6	6	116.58	下1排
	Φ10		3860	27	27	64.30	@200(6)1跨27
	Φ10		2460	54	54	81.96	1跨54
	Φ8		1100	26	26	11.30	
CTL-1 (42-#)	Φ22		6390	6*2	12	228.51	上1排(通长)










































构件名称	级直 别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备 注
	Φ14	 4700	4700	4*2	8	45.50	腰筋
	Φ22	 6040	6390	6*2	12	228.51	下1排
	Φ10	 920	3860	22*2	44	104.79	@200(6)1跨22
	Φ10	 920	2460	44*2	88	133.57	1跨44
	Φ8	 940	1100	20*2	40	17.38	
CTL-1 (43-#)	Φ22	 4740	5090	6	6	91.01	上1排(通长)
	Φ14	 3400	3400	4	4	16.46	腰筋
	Φ22	 4740	5090	6	6	91.01	下1排
	Φ10	 920	3860	15	15	35.72	@200(6)1跨15
	Φ10	 920	2460	30	30	45.53	1跨30
	Φ8	 940	1100	14	14	6.08	
CTL-1 (44-#)	Φ22	 4620	4970	6	6	88.86	上1排(通长)
	Φ14	 3080	3080	4	4	14.91	腰筋
	Φ22	 4620	4970	6	6	88.86	下1排
	Φ10	 920	3860	14	14	33.34	@200(6)1跨14
	Φ10	 920	2460	28	28	42.50	1跨28
	Φ8	 940	1100	12	12	5.21	
CTL-1 (45-#)	Φ22	 8220	8570	6	6	153.23	上1排(通长)
	Φ14	 6680	6680	4	4	32.33	腰筋(通长)
	Φ22	 8220	8570	6	6	153.23	下1排(通长)
	Φ10	 920	3860	27	27	64.30	@200(6)1跨13,2跨14
	Φ10	 920	2460	54	54	81.96	1跨26,2跨28
	Φ8	 940	1100	22	22	9.56	








构件名称	级直别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备注
CTL-1 (46-#)	Φ22		4580	6*2	12	163.78	上1排(1跨)
	Φ28		3750	7*2	14	253.57	洞口上部加筋
	Φ22		2700	6*2	12	96.55	上1排(2跨)
	Φ14		7450	4*2	8	72.12	腰筋(通长)
	Φ22		3000 6190	6*2	12	328.63	下1排(通长) 长:8790 对:40
	Φ10		3860	27*2	54	128.61	@200(6)1跨18,2跨9
	Φ10		2460	54*2	108	163.92	1跨36,2跨18
	Φ12		3900	18*2	36	124.68	洞口@100
	Φ12		2460	36*2	72	157.28	洞口@100
	Φ8		1100	40*2	80	34.76	
CTL-1 (47-#)	Φ22		3880	6	6	69.37	上1排(1跨)
	Φ25		3750	6	6	86.62	洞口上部加筋
	Φ22		3380	6	6	60.43	上1排(2跨)
	Φ14		7450	4	4	36.06	腰筋(通长)
	Φ22		3000 6190	6	6	164.32	下1排(通长) 长:8790 对:40
	Φ10		3860	27	27	64.30	@200(6)1跨15,2跨12
	Φ10		2460	54	54	81.96	1跨30,2跨24
	Φ12		3900	18	18	62.34	洞口@100
	Φ12		2500	36	36	79.92	洞口@100
	Φ8		1100	40	40	17.38	
CTL-1 (48-#)	Φ22		4890	6*2	12	174.87	上1排(通长)
	Φ14		3200	4*2	8	30.98	腰筋
	Φ25		4940	8*2	16	304.30	下1排

构件名称	级直别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备注
	Φ12	 920	3900	27*2	54	187.01	@100(6)1跨27
	Φ12	 920	2500	54*2	108	239.76	1跨54
	Φ8	 940	1100	26*2	52	22.59	
CTL-1 (49-#)	Φ22	220  220	8070	6	6	144.29	上1排(通长)
	Φ14	 7070	7070	4	4	34.22	腰筋
	Φ25	250  3350	3550	8	8	109.34	洞口下部加筋
	Φ22	 220	5500	6	6	98.34	下1排
	Φ10	 920	3860	28	28	66.69	@200(6)1跨28
	Φ10	 920	2460	56	56	85.00	1跨56
	Φ12	 920	3900	14	14	48.48	@100(6)1跨14
	Φ12	 920	2500	28	28	62.16	1跨28
	Φ8	 940	1100	40	40	17.38	
CTL-1 (50-#)	Φ22	220  220	3700	6	6	66.16	上1排(通长)
	Φ14	 3350	3350	4	4	16.21	腰筋
	Φ22	220  220	3700	6	6	66.16	下1排
	Φ10	 920	3860	18	18	42.87	@200(6)1跨18
	Φ10	 920	2460	36	36	54.64	1跨36
	Φ8	 940	1100	16	16	6.95	
CTL-1 (51-#)	Φ22	220  220	7670	6	6	137.14	上1排(通长)
	Φ14	 6650	6650	4	4	32.19	腰筋
	Φ25	250  3350	3550	8	8	109.34	洞口下部加筋
	Φ22	 220	5100	6	6	91.19	下1排
	Φ10	 920	3860	26	26	61.92	@200(6)1跨26

构件名称	级直别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备注
	Φ10	 920	2460	52	52	78.93	1跨52
	Φ12	 920	3900	14	14	48.48	@100(6)1跨14
	Φ12	 920	2500	28	28	62.16	1跨28
	Φ8	 940	1100	40	40	17.38	
CTL-1 (52-#)	Φ22	 2950	3300	6	6	59.00	上1排(通长)
	Φ14	 2950	2950	4	4	14.28	腰筋
	Φ22	 2950	3300	6	6	59.00	下1排
	Φ10	 920	3860	16	16	38.11	@200(6)1跨16
	Φ10	 920	2460	32	32	48.57	1跨32
	Φ8	 940	1100	14	14	6.08	
CTL-1 (53#-55#)	Φ22	 1850	2030	6	6	36.30	上1排(1跨)6
	Φ28	 5550	5550	6	6	160.84	53#洞口上部加筋
	Φ28	 5200	5390	3	3	78.10	53#洞口上部加筋
	Φ22	 9000 对 300	9000 300	5	5	138.57	上1排(2跨)3,(2跨)2 长:9260 对:40
	Φ28	 3700	3700	8	8	142.97	55#洞口上1排加筋
	Φ28	 3750	3940	4	4	76.12	55#洞口上1排加筋
	Φ28	 3700	3700	1	1	17.87	55#洞口上2排加筋
	Φ28	 3750	3940	1	1	19.03	55#洞口上2排加筋
	Φ22	 3250	3430	6	6	61.33	上1排(3跨)2,(3跨)4
	Φ14	 4750	4750	4	4	22.99	腰筋(1跨)2,(3跨)2
	Φ14	 9000 9000 950 搭 搭	9000 9000 950	2	2	45.86	腰筋(通长) 长:18510 搭:220
	Φ14	 8050	8050	2	2	19.48	腰筋(2跨)
	Φ22	 6100	6450	2	2	38.44	下1排(53#)1,(55#)1

构件名称	级直 别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备 注
	Φ22	220   8820 9000 2280   220 单 对	9000 9000 2460	5	5	304.85	下1排(通长)5 长:19840 单:220,对:40
	Φ10	 920	3860	14	14	33.34	@200(6)53#5,55#9
	Φ10	 920	2460	28	28	42.50	53#10,55#18
	Φ10	 920	3260	38	38	76.43	@200(4)54#38
	Φ10	 920	2680	38	38	62.84	54#38
	Φ12	 920	3900	22	22	76.19	@100(6)53#,22
	Φ12	 920	2380	44	44	92.99	53#44
	Φ12	 920	3900	14	14	48.48	@100(6)55#,14
	Φ12	 920	2500	28	28	62.16	55#28
	Φ8	 640	800	44	44	13.90	
	Φ8	 940	1100	14	14	6.08	
CTL-1 (56#-2)	Φ22	220   6240   220	6590	6*2	12	235.66	上1排(通长)
	Φ14	4900	4900	4*2	8	47.43	腰筋
	Φ22	220   6240   220	6590	6*2	12	235.66	下1排
	Φ10	 920	3860	23*2	46	109.55	@200(6)1跨23
	Φ10	 920	2460	46*2	92	139.64	1跨46
	Φ8	 940	1100	20*2	40	17.38	
CTL-3a (57-#)	Φ25	250   8800 300   250 套	9000 500	5	5	182.87	上1排(通长) 长:9100
	Φ14	9100	9100	4	4	44.04	腰筋
	Φ25	250   8800 300   250 套	9000 500	5	5	182.87	下1排 长:9100
	Φ10	 920	3060	47	47	88.74	@200(4)1跨47
	Φ10	 920	2620	47	47	75.98	1跨47
	Φ8	 540	700	44	44	12.17	

构件名称	级直别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备注
CTL-3 (58-#)	Φ22		3740	4*2	8	89.16	上1排(通长)
	Φ14		2750	4*2	8	26.62	腰筋
	Φ22		3740	4*2	8	89.16	下1排
	Φ10		3060	12*2	24	45.31	@200(4)1跨12
	Φ10		2420	12*2	24	35.84	1跨12
	Φ8		700	10*2	20	5.53	
CTL-1 (59-#)	Φ22		8190	6*2	12	292.87	上1排(通长)
	Φ14		6500	4*2	8	62.92	腰筋
	Φ22		8190	6*2	12	292.87	下1排
	Φ10		3860	31*2	62	147.66	@200(6)1跨31
	Φ10		2460	62*2	124	188.21	1跨62
	Φ8		1100	28*2	56	24.33	
CTL-1 (60-#)	Φ22		6520	6	6	116.58	上1排(通长)
	Φ14		5500	4	4	26.62	腰筋
	Φ22		6520	6	6	116.58	下1排
	Φ10		3860	27	27	64.30	@200(6)1跨27
	Φ10		2460	54	54	81.96	1跨54
	Φ8		1100	26	26	11.30	
CTL-1 (61-#)	Φ22		6390	6*2	12	228.51	上1排(通长)
	Φ14		4700	4*2	8	45.50	腰筋
	Φ22		6390	6*2	12	228.51	下1排
	Φ10		3860	22*2	44	104.79	@200(6)1跨22
	Φ10		2460	44*2	88	133.57	1跨44

构件名称	级直 别径	钢筋简图	下料 (mm)	根件 数*数	总 根数	重量 (kg)	备 注
	Φ8		1100	20*2	40	17.38	
CTL-1 (62-#)	Φ22		3520	6*3	18	188.81	上1排(通长)
	Φ14		2500	4*3	12	36.30	腰筋
	Φ22		3520	6*3	18	188.81	下1排
	Φ10		3860	12*3	36	85.74	@200(6)1跨12
	Φ10		2460	24*3	72	109.28	1跨24
	Φ8		1100	10*3	30	13.04	